A Well-know Trademark in China

The Tire Supplier of World Rally Championship

DURUN·盾轮®

DURUN TIRE PRODUCT CATALOG

2012 Edition

DURUN·盾轮®

ShanDong Yongtai Chemical Group Co.,Ltd.

Tel:800-860-9018

http://www.yongtaigroup.com

DURUN TIRE PRODUCT CATALOG

Acontents

Introduction ····· 01–02
M626 ····· 01–02
M636 ····· 03–04
FA18 ····· 03–04
B717 ····· 05–06
T90A ····· 05–06
SPORT–ONE ····· 07–08
A–ONE ····· 09–10
F–ONE ····· 11–12
A2000 ····· 13–14
D2009 ····· 15–16
D108 ····· 17–18
SW01 ····· 17–18
C212 ····· 19–20
C222 ····· 19–20
K323 ····· 21–22
K324 ····· 21–22
K333 ····· 23–24
YTR08 ····· 23–24
MT ····· 25–26
YTR10 ····· 25–26
YTH1 ····· 27–28
YTH2 ····· 27–28
YTH3 ····· 29–30
YTH4 ····· 29–30
YTH5 ····· 31–32
YTH6 ····· 31–32
YTH7 ····· 33–34
YTH8 ····· 33–34
YTH9 ····· 35–36
YTH10 ····· 35–36
YTH12 ····· 37–38
YTH13 ····· 37–38
YTH15 ····· 39–40
YTH16 ····· 39–40
YT901 ····· 41–42
YT902 ····· 41–42
YT903 ····· 43–44
YT905 ····· 43–44
YT906 ····· 45–46
YT101 ····· 45–46
YT102 ····· 47–48
Memorandum ····· 47–48

DURUN·盾轮®

DURUN TIRE PRODUCT CATALOG

Shandong Yongtai Chemical Group Co., Ltd

Introduction

Shandong Yongtai Chemical Group Co,Ltd. is a leading tire manufacturer utilizing international advanced technologies in its production of series of radial tire. It produces DURUN , GOLDWAY and BANNERS brand Ultra High Performance tire, Passenger Car Radial tire, Medium Radial Truck tire , Snow radial tire and All -steel radial tire . It can provide clients with more than 300 sizes of tire, and the new specifications of tire are added constantly each year. The company invested most advanced production and testing equipments imported from the United States ,Germany, Netherlands. Italy, Japan and other countries. The products have been successfully certified by E-MARK, E-S-MARK, the United States DOT, Brazil INMETRO. ISO/TS-16949, CCC certification, and other domestic and international quality system certification.

ULTRA HIGH PERFORMANCE RADIAL TIRE

M626

Treadwear	320
Traction	A
Temperature	A

SIGNIFICANT FEATURES

- Super solid structural design, shock-resistant and strong wear resistant.
- Wide and enclosed-type shoulder design improves grip on wet road.
- Wide tire running area makes for balance road contact,giving a comfort and Endurable riding.
- Tough bead design endows tires with good cornerning and control capability on road.
- Belt plies composed of steel wires reinforce body plies and increase safety Performance.

Size	Load. Index	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
265/45ZR21	104	W	91/2J	900	300	271	771	644	10
265/45R21	104	V	91/2J	900	300	271	771	644	10
295/35ZR21	107	WXL	101/2J	975	340	301	740	671	10
295/35ZR21	107	YXL	101/2J	975	340	301	740	671	10
295/40ZR21	111	WXL	101/2J	1090	340	301	768	647	10
295/40ZR21	107	W	101/2J	975	300	301	768	647	10
295/40R21	111	VXL	101/2J	1090	340	301	768	647	10
295/40R21	107	V	101/2J	975	300	301	768	647	10
265/30R22	97	VXL	91/2J	730	340	271	719	691	10
265/30ZR22	97	WXL	91/2J	730	340	271	719	691	10
285/30R22	101	VXL	10J	825	340	290	731	680	10
295/25ZR22	97	WXL	101/2J	703	340	301	707	703	10
295/25R22	97	VXL	101/2J	703	340	301	707	703	10
295/30ZR22	103	WXL	101/2J	875	340	301	737	674	10
305/45R22	118	VXL	10J	1320	340	300	833	596	10
305/45R22	118	HXL	10J	1320	340	300	833	596	10
305/45ZR22	118	WXL	10J	1320	340	300	833	596	10
245/30ZR24	94	WXL	9J	670	340	236	758	655	10
275/30ZR24	101	WXL	10J	825	340	278	775	641	11
295/30R24	105	VXL	101/2J	925	340	301	788	630	10
255/30ZR26	99	WXL	9J	775	340	261	814	696	10
255/25ZR28	95	WXL	9J	690	340	260	839	592	10
275/25ZR28	99	WXL	10J	775	340	283	849	585	10
295/25ZR28	103	WXL	101/2J	875	340	301	859	578	10
255/30R30	104	VXL	9J	850	340	260	916	542	10
265/30R30	106	WXL	91/2J	950	340	271	922	539	10
285/50R20	116	VXL	9J	1520	340	297	794	665	10
285/50R20	112	V	9J	1120	300	297	794	665	10
295/35ZR21	17	WXL	101/2J	975	340	301	711	742	10
295/35ZR21	107	YXL	101/2J	975	340	301	711	742	10
235/35ZR20	92	WXL	81/2J	630	340	241	672	785	10
235/35ZR20	88	W	81/2J	560	300	241	672	785	10
265/45ZR20	108	WXL	9J	1000	340	266	746	707	10
265/45ZR20	104	W	9J	900	300	266	746	707	10
285/30ZR20	99	WXL	10J	775	340	290	680	776	10
285/30ZR20	95	W	10J	690	300	290	680	776	10
285/30R20	99	VXL	10J	775	340	290	680	776	10

ULTRA HIGH PERFORMANCE RADIAL TIRE

M636

Treadwear	320
Traction	A
Temperature	A

SIGNIFICANT FEATURES

- Asymmetric pattern reflects not only noble, but also improve the comfort, speed and ease of handling.
- Four main patterns of drainage ditch to increase the drainability capacity of the tire.
- Angle arc region of the tread block, effectively scratch surface water film and provides excellent grip.
- More accurate cornering, and better control of the vehicle.

Size	Load. Index	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
205/40ZR17	80	W	71/2J	450	300	212	596	834	10
205/40ZR17	84	WXL	71/2J	500	340	212	596	834	10
215/40ZR17	83	W	71/2J	487	300	218	604	823	10
215/40ZR17	83	Y	71/2J	487	300	218	604	823	10
215/40ZR17	87	WXL	71/2J	545	340	218	604	823	10
215/45ZR17	87	W	7J	545	300	213	626	794	10
215/45ZR17	91	WXL	7J	615	340	213	626	794	10
215/50ZR17	95	WXL	7J	690	340	226	648	767	10
225/45ZR17	91	W	71/2J	615	300	225	634	784	10
225/45R17	91	V	71/2J	615	300	225	634	784	10
225/45ZR17	94	WXL	71/2J	670	340	225	634	784	10
225/45R17	94	VXL	71/2J	670	340	225	634	784	10
225/50R17	94	V	7J	670	300	233	685	725	10
225/55ZR17	101	WXL	8J	825	340	233	680	731	10
245/55R17	102	V	71/2J	850	300	253	702	708	10
205/50R17	89	V	61/2J	580	300	214	638	779	10
205/50R17	93	VXL	61/2J	650	340	214	638	779	10
215/40ZR18	89	WXL	71/2J	580	340	218	629	790	10
225/40ZR18	88	W	8J	560	300	230	637	780	10
225/40ZR18	88	Y	8J	560	300	230	637	780	10
225/40ZR18	92	WXL	8J	630	340	230	637	780	10
245/40ZR18	97	WXL	81/2J	730	340	248	653	761	10
235/35ZR19	91	WXL	81/2J	615	340	241	647	816	10
235/35ZR19	91	YXL	81/2J	615	340	241	647	816	10
235/35ZR19	87	W	81/2J	545	300	241	647	816	10
235/35ZR19	87	Y	81/2J	545	300	241	647	816	10
235/40ZR18	95	WXL	81/2J	690	340	241	645	818	10
235/40ZR18	91	W	81/2J	615	300	241	645	818	10

Remark:The sizes with green mark will be available in 2012.

ULTRA HIGH PERFORMANCE RADIAL TIRE

F18A

Treadwear	320
Traction	A
Temperature	A

SIGNIFICANT FEATURES

- Streamlined design patterns to improve the overall speed and handle of the tire.
- Flow patterns to minimize the noise, and make driving more comfortable.
- Fine tread designed pattern make driving experience very comfortable.
- Sharp corners of the middle tread pattern, the first time to puncture water film.

Size	Load. Index	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
215/35ZR18	84	WXL	71/2J	500	340	218	607	818	10
215/40ZR18	89	WXL	71/2J	580	340	218	629	790	10
225/40ZR18	88	W	8J	560	300	230	637	780	10
225/40ZR18	92	WXL	8J	630	340	230	637	780	10
235/40ZR18	95	WXL	81/2J	690	340	241	645	770	10
235/40ZR18	9	W	81/2J	615	300	241	645	770	10
245/40ZR18	97	WXL	81/2J	730	340	248	653	761	10
245/45ZR18	100	WXL	8J	800	340	243	677	734	10
245/35R19	93	WXL	81/2J	650	340	248	655	806	10

Remark:The sizes with yellow mark will be available in 2013.

PASSENGER CAR RADIAL TIRE

B717

Treadwear	320
Traction	A
Temperature	A

SIGNIFICANT FEATURES

- Small and delicate tread pattern to ensure comfort driving, to minimize the noise.
- Central pattern for excellent handling and designed to shorten the braking distance.
- Side of the trench to improve control in the wet and dry roads, to prevent the tire performance degradation on the wet ground.
- Four drain to ensure the safety on wet ground.

Size	Load. Index	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
175/65R14	82	H	5J	475	300	177	584	851	10
175/65R14	84	H	5J	530	300	177	584	851	10
●185/60R14	82	H	51/2J	475	300	189	578	860	10
185/60R14	86	HXL	51/2J	530	340	189	578	860	10
●185/65R14	86	H	51/2J	530	300	189	596	834	10
●185/65R14	90	HXL	51/5J	600	340	189	596	834	10
195/60R14	86	H	6J	530	300	201	590	842	10
195/60R14	86	V	6J	530	300	201	590	842	10
●185/65R15	88	H	51/2J	560	300	189	621	800	10
●185/65R15	88	V	51/2J	560	300	189	621	800	10
195/50R15	82	V	6J	475	300	201	577	861	10
195/50R15	82	H	6J	475	300	201	577	861	10
195/55R15	85	V	6J	515	300	201	595	835	10
195/55ZR15	85	W	6J	515	300	201	595	835	10
●195/60R15	88	H	6J	560	300	201	615	808	10
●195/60R15	88	V	6J	560	300	201	615	808	10
●195/65R15	95	HXL	6J	690	340	201	635	782	10
●195/65R15	95	VXL	6J	690	340	201	635	782	10
●195/65R15	91	V	6J	615	300	201	635	782	10
●195/65R15	91	H	6J	615	300	201	635	782	10
205/55R16	91	V	61/2J	615	300	214	632	835	10
205/55R16	94	VXL	61/2J	670	340	214	632	835	10
205/55ZR16	91	W	61/2J	615	300	214	632	835	10
205/55ZR16	94	WXL	61/2J	670	340	214	632	835	10
185/70R14	92	TXL	51/2J	630	340	189	616	857	10
185/70R14	88	H	51/2J	560	300	189	616	857	10
185/70R14	88	T	51/2J	560	300	189	616	857	10
205/65R15	94	H	6J	670	300	209	647	816	10
205/65R15	94	V	6J	670	300	209	647	816	10
205/50ZR16	87	W	61/2J	545	300	214	612	862	10
205/50R16	87	V	61/2J	545	300	214	612	862	10
175/70R14	88	TXL	5J	560	340	177	602	877	10
175/70R14	84	T	5J	500	300	177	602	877	10
195/70R14	95	TXL	6J	690	340	201	630	838	10
195/70R14	91	T	6J	615	300	201	630	838	10
175/70R13	82	T	5.00B	475	300	177	576	916	10
175/70R13	82	H	5.00B	475	300	177	576	916	10

Remark:The sizes with green mark will be available in 2012.

PASSENGER CAR RADIAL TIRE

T90A

Treadwear	720
Traction	A
Temperature	A

SIGNIFICANT FEATURES

- High tread reinforcing, high strength matrix material, so that it has excellent wear resistance and long life.
- Shoulder side of the horizontal pattern tire for wet and dry road condition.
- Distance and angle precision tread pattern design, effectively reduce tire noise.
- Two-way symmetrical tread pattern, perfect touchdown, with a strong grip.

Size	Load. Index	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
●175/50R13	72	V	5.50B	355	250	182	506	1043	11
●175/50R13	76	HXL	5.50B	400	290	182	506	1043	11
●165/60R12	71	H	5.00B	345	250	170	503	1049	11
185/60R14	82	H	51/2J	475	300	189	578	913	11
185/60R14	86	HXL	51/2J	530	340	189	578	913	11
●195/60R14	86	H	6J	530	300	157	590	894	11
155/65R13	73	T	4.50B	365	250	170	532	992	11
165/65R13	77	Q	5.00B	412	300	189	544	970	11
●185/65R14	86	H	51/2J	530	300	189	596	885	11
●185/65R14	90	HXL	51/2J	600	340	150	596	885	11
145/70R12	69	Q	4.50B	325	250	157	509	1037	11
155/70R13	75	S	4.50B	387	300	170	548	963	11
165/70R13	79	T	5.00B	437	300	170	562	939	11
165/70R13	83	TXL	5.00B	487	340	170	562	939	11
165/70R14	81	T	5J	462	300	189	588	897	11
●185/70R14	88	T	51/2J	560	300	189	616	857	11
●185/70R14	92	TXL	51/2J	630	340	201	616	857	11
●195/70R14	95	TXL	6J	690	340	201	630	838	11
●195/70R14	91	T	6J	615	300	201	630	838	11
215/75R15	100	S	6J	800	250	216	703	751	11
155/80R13	79	T	4.50B	437	240	157	578	913	11
155/80R13	83	TXL	4.50B	487	280	157	578	913	11
●165/80R13	83	T	4.50B	487	240	165	594	888	11
●165/80R13	87	TXL	4.50B	545	280	165	594	888	11

Remark:The sizes with yellow mark will be available in 2013.

ULTRA HIGH PERFORMANCE RADIAL TIRE

SPORT-ONE

Treadwear	320
Traction	A
Temperature	A

DIRECTIONAL

SIGNIFICANT FEATURES

- 'V'-type Directional tread pattern provide high-speed driving response and stability, aquaplaning resistance and quiet driving conditions.
- Greater contact patch ratio delivers enchanced driving response in the dry and improved drainage capability.
- Shoulder area sub groove delivers reduced tire noise,improved grip when cornering in the wet and allows Excess heat to escape.
- Endless full cap ply Allows high-speed driving endurance by fastening belt edge area while driving.
- At high-speeds conditions.

Size	Load. Index	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
225/35ZR20	90	W	8J	600	340	230	666	746	10
225/35ZR20	93	WXL	8J	650	340	230	666	746	10
245/35ZR20	95	WXL	81/2J	690	340	248	680	731	10
255/35ZR20	97	WXL	9J	730	350	260	686	724	10
255/35ZR20	97	YXL	9J	730	350	260	686	724	10
205/40ZR17	80	W	71/2J	450	300	212	596	834	10
205/40ZR17	84	WXL	71/2J	500	340	212	596	834	10
215/40ZR17	83	W	71/2J	487	250	218	604	823	10
215/40ZR17	87	WXL	71/2J	545	340	218	604	823	10
225/40ZR18	88	W	8J	560	250	230	637	780	10
225/40ZR18	92	WXL	8J	630	300	230	637	780	10
235/40ZR18	91	W	81/2J	615	300	241	645	770	10
235/40ZR18	95	WXL	81/2J	690	340	241	645	770	10
215/45ZR17	87	W	7J	545	250	213	626	794	10
215/45ZR17	91	WXL	7J	615	340	213	626	794	10
225/45ZR17	94	WXL	71/2J	670	340	225	634	784	10
235/45ZR17	97	WXL	8J	730	350	236	644	771	10
235/45ZR17	94	W	8J	670	300	236	644	771	10
195/45ZR16	84	WXL	61/2J	500	340	200	582	854	10
195/45R15	78	V	61/2J	425	250	195	557	892	10
195/50R15	82	V	6J	475	300	201	577	861	10
215/40ZR18	89	WXL	71/2J	580	350	218	629	790	10

ULTRA HIGH PERFORMANCE RADIAL TIRE

A-ONE

Treadwear 320
Traction A
Temperature A

DIRECTIONAL

SIGNIFICANT FEATURES

- Center straight-ling rib The continuous grouding on the road helps straight running stability at High speed.excellent steering response in unexpected hangdling.
- The cured conversion of running directional groove edge The curved conversion from the edge spot of groove on running direction.
- Grounding pressure distribution of block.
- Arrangement of the variable pitch 5 optimized sizes of tread block can disperse and reduce noise from the tire. It realizes the quiet riding.
- Running direction groove The optimized 4/3 grooves enhance both The performance of drainage on the wet Road and the efficiency of high speed Driving by reducing water pressure On the grounding spot.

Size	Load. Index	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
215/35ZR18	84	WXL	71/2J	500	350	218	607	818	10
205/40ZR17	80	W	71/2J	450	300	212	596	834	10
205/40ZR17	84	WXL	71/2J	500	340	212	596	834	10
205/40ZR17	83	W	71/2J	487	250	218	604	823	10
215/40ZR17	87	WXL	71/2J	545	340	218	604	823	10
225/40ZR18	88	W	8J	560	250	230	637	780	10
225/40ZR18	92	WXL	8J	630	300	230	637	780	10
215/45ZR17	87	W	7J	545	250	213	626	794	10
215/45ZR17	91	WXL	7J	615	340	213	626	794	10
195/50R15	82	V	6J	475	300	201	577	861	10
205/50R16	87	V	61/2J	545	300	214	612	812	10
205/50ZR16	87	W	61/2J	545	300	214	612	812	10
225/50R16	92	V	7J	630	300	233	632	786	10
225/50ZR16	92	W	7J	630	300	233	632	786	10
195/55R15	85	V	6J	515	250	201	595	835	10
195/55ZR15	85	W	6J	515	250	201	595	835	10
205/55R16	91	V	61/2J	615	300	214	632	786	10
205/55ZR16	91	W	61/2J	615	300	214	632	786	10
205/55ZR16	94	WXL	61/2J	670	340	214	632	786	10
225/55R16	95	V	7J	690	250	233	654	760	10
225/55R16	99	VXL	7J	775	340	233	654	760	10
225/55ZR16	95	W	7J	690	250	233	654	760	10
225/55ZR16	99	WXL	7J	775	340	233	654	760	10
225/55ZR17	101	WXL	8J	825	350	233	680	731	10
215/55R16	97	VXL	7J	730	340	226	642	774	10
215/55ZR16	97	WXL	7J	730	340	226	642	774	10
235/55R17	103	VXL	71/2J	875	350	245	715	695	10
225/60R16	98	H	61/2J	750	250	228	676	735	10
205/65R15	94	H	6J	670	300	209	647	768	10
235/35ZR19	87	Y	81/2J	545	290	241	647	768	10
235/35ZR19	91	WXL	81/2J	615	350	241	647	768	10
235/35ZR19	91	YXL	81/2J	615	350	241	647	768	10
235/35ZR19	87	W	81/2J	545	290	241	647	768	10

ULTRA HIGH PERFORMANCE RADIAL TIRE

F-ONE

Treadwear 320
Traction A
Temperature A

DIRECTIONAL

SIGNIFICANT FEATURES

- Endless full Cap ply Allows high-speed driving endurance by fastening belt edge area while driving At high-speed conditions.
- Rim Protector Helps to protect against wheel damage from accidental contact with curb.
- 'V'-type Directional Tread Pattern Provide excellent water drainage and resist aquaplaning.
- Continuous Center Tread Rib Enhances high-speed driving stability.
- Silica Compound Improves wet and dry traction and remains pliable at low temperature.
- Variable pitch Sequence Reduces pattern Noise Further by Optimization of pitch Sequences for A quiet ride.

Size	Load. Index	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
255/30ZR22	95	WXL	9J	690	340	260	713	697	11
255/30ZR24	97	WXL	91/2J	730	350	261	764	650	11
255/30R24	97	VXL	91/2J	730	350	260	764	650	11
245/35ZR19	93	WXL	81/2J	650	350	248	655	758	10
245/35ZR19	93	YXL	81/2J	650	350	248	655	758	10
225/35ZR20	90	W	8J	600	340	230	666	746	10
225/35ZR20	93	WXL	8J	650	340	230	666	746	10
245/35ZR20	95	YXL	81/2J	690	340	248	680	731	10
245/35ZR20	95	WXL	81/2J	690	340	248	680	731	10
255/35ZR20	97	WXL	9J	730	350	260	686	724	10
255/35ZR20	97	YXL	9J	730	350	260	686	724	10
265/35R22	102	VXL	91/2J	850	340	271	745	667	11
305/35ZR24	114	WXL	11J	1180	340	313	824	603	11
235/40ZR18	91	W	81/2J	615	300	241	645	770	10
235/40ZR18	95	WXL	81/2J	690	340	241	645	770	10
305/40R22	114	VXL	11J	1180	290	313	803	619	11
235/45ZR17	97	WXL	8J	730	350	236	644	771	10
235/45ZR17	94	W	8J	670	300	236	644	771	10
235/30ZR22	90	WXL	81/2J	600	340	241	702	708	11
235/30ZR22	90	YXL	81/2J	600	340	241	702	708	11
245/30ZR22	92	WXL	81/2J	630	340	248	706	704	11
245/30ZR22	92	YXL	81/2J	630	340	248	706	704	11
265/40ZR22	106	WXL	91/2J	950	340	270	770	645	11
265/40R22	106	VXL	91/2J	950	340	270	770	645	11
275/25ZR24	96	WXL	10J	710	350	278	746	666	11
275/25ZR26	98	W	10J	750	350	282	800	621	11
285/35ZR22	106	WXL	10J	950	340	285	760	654	11
285/35R22	106	VXL	10J	950	340	285	760	654	11
295/30ZR26	107	WXL	101/2J	975	340	301	838	593	11
295/30R26	107	VXL	101/2J	975	340	301	838	593	11
305/30ZR26	109	WXL	11J	1030	340	305	845.5	588	11
305/30R26	109	VXL	11J	1030	340	313	844	589	11
295/35R24	110	VXL	101/2J	1060	340	301	816	609	11
295/35ZR24	110	WXL	101/2J	1060	340	301	816	609	11
275/40ZR20	106	WXL	91/2J	950	340	272	728	682	10
275/40R20	106	VXL	91/2J	950	340	272	728	682	10
275/45ZR20	110	WXL	9J	1060	340	272	756	657	11
275/45R20	110	VXL	9J	1060	340	272	756	657	11
225/30ZR20	85	WXL	8J	515	340	230	644	771	10
225/30ZR20	85	YXL	8J	515	340	230	644	771	10
275/55R20	117	SXL	81/2J	1285	340	284	808	615	10
275/55R20	117	VXL	81/2J	1285	340	284	808	615	10

PASSENGER RADIAL TIRE

A2000

Treadwear	440
Traction	A
Temperature	A

DIRECTIONAL

SIGNIFICANT FEATURES

- All-season high performance tread design. Uniform contact pressure offers a stable and comfortable riding.
- Outstanding handling performance on wet road.
- Unique arc-shaped pattern with strong dynamic and sportly looking feature at high speed driving.

Size	Load. Index	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
185/60R14	82	H	51/2J	475	250	189	578	860	10
195/60R14	86	H	6J	530	250	201	590	842	10
195/60R15	88	H	6J	560	300	201	615	808	10
195/60R15	88	V	6J	560	300	201	615	808	10
205/60R15	91	H	6J	615	250	209	627	792	10
205/60R15	91	V	6J	615	250	209	627	792	10
205/60R15	95	HXL	6J	690	290	209	627	792	10
215/60R16	95	H	61/2J	690	300	221	664	748	10
215/60R16	95	V	61/2J	690	300	221	664	748	10
195/65R15	95	HXL	6J	690	290	201	635	782	10
195/65R15	95	VXL	6J	690	290	201	635	782	10
205/65R15	94	HH	6J	670	300	209	647	768	11
185/65R14	86	H	51/2J	530	250	189	596	834	10
175/65R14	82	H	5J	475	250	177	584	851	10
175/65R14	84	HXL	5J	530	290	177	584	851	10
215/65R15	100	H	61/2J	800	350	221	662	750	10
215/65R15	96	Q	61/2J	710	250	221	662	750	10
145/70R12	69	H	4.50B	325	250	150	509	976	9
175/70R13	82	T	5J	475	250	177	576	862	10
175/70R13	82	TXL	5J	475	250	177	576	862	10
195/70R14	95	T	6J	690	300	201	630	789	10
195/70R14	91	TXL	6J	615	250	201	630	789	10
205/70R14	98	T	6J	750	250	212	644	771	10
185/70R14	88	T	51/2J	560	250	189	616	806	10
165/70R13	79	TXL	5.00B	437	250	170	562	884	10
165/70R13	83	Q	5.00B	487	300	170	562	884	10
165/70R13C	88/86	T	5.00B	560/530	375	170	562	884	10
175/70R14	84	TXL	5J	500	250	177	602	825	10
175/70R14	88	Q	5J	560	290	177	602	825	10
205/70R15	96	T	6J	710	250	209	669	743	10
205/70R15	96	S	6J	710	250	209	669	743	10
215/70R15	97	R	61/2J	730	250	221	684	726	10
195/70R15C	104/102	Q	61/2J	900/850	450	201	655	758	10
195/70R15C	98/96	Q	61/2J	750/710	325	201	655	758	10
165/65R13	77	S	5.00B	412	250	170	544	913	10
155/70R13	75	S	4.50B	387	250	157	548	907	10
215/75R15	100	V	6J	800	250	216	703	707	10
195/65R15	91	H	6J	615	250	201	635	782	10
185/65R15	88	V	51/2J	560	250	189	621	800	10
185/65R15	88		51/2J	560	250	189	621	800	10

SNOW RADIAL TIRE

D2009

DIRECTIONAL

SIGNIFICANT FEATURES

The D2009 snow pattern is newly designed and prouduced in 2009,which has excellent anti-skiding performance under low temperture and strong grasping performance.and excellent handling performance. The special design and tread compound can effectively enhance the performance of the tire grip to ensure safe driving in winter season.

Size	Load. Index	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
165/70R13	79	T	6.00B	437	250	170	562	884	11
215/75R15	100	S	6J	800	300	216	703	751	11
235/65R16	103	T	7J	875	300	240	712	741	11
225/70R16	103	S	61/2J	875	300	228	722	731	11
225/70R16	103	T	61/2J	875	300	228	722	731	11
235/75R15	105	T	61/2J	925	300	235	733	720	11
235/75R15	105	S	61/2J	925	300	235	733	720	11
235/75R15	105	Q	61/2J	925	300	235	733	720	11
245/45R17	99	SXL	8J	775	340	243	652	809	11
235/70R16	107	S	7J	975	300	240	736	717	11
235/70R16	106	T	7J	950	300	240	736	717	11
215/70R16	101	Q	61/2J	825	300	221	708	745	11
265/70R17	115	S	8J	1215	300	272	804	656	11
245/75R16	111	S	7J	1090	300	248	774	682	11
225/60R16	98	T	61/2J	750	300	228	676	735	11
215/70R15	98	T	61/2J	750	300	221	683	727	12
225/60R17	99	H	61/2J	775	300	228	702	708	11
205/70R15	96	T	6J	710	300	209	669	743	11

Size	Load. Index	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
225/45R17	94	VXL	71/2J	670	340	225	634	784	12
225/45R17	94	HXL	71/2J	670	340	225	634	784	12
225/45R17	90	H	71/2J	600	300	225	634	784	12
195/50R15	82	V	6J	475	300	201	577	861	12
195/50R15	82	H	6J	475	300	201	577	861	12
205/55R16	91	V	61/2J	615	300	214	632	786	12
205/55R16	91	H	61/2J	615	300	214	632	786	12
195/60R15	88	H	6J	560	300	201	615	808	11
195/60R15	88	T	6J	560	300	201	615	808	11
205/60R15	91	T	6J	615	250	209	627	792	11
205/60R15	91	H	6J	615	250	209	627	792	11
195/65R15	91	T	6J	615	250	201	635	782	12
195/65R15	91	H	6J	615	250	201	635	782	12
195/65R15	95	HXL	6J	690	290	201	635	782	12
195/65R15	95	TXL	6J	690	290	201	635	782	12
195/65R15	95	VXL	6J	690	290	201	635	782	12
205/65R15	94	H	6J	670	300	209	647	768	12
205/65R15	94	V	6J	670	300	209	647	768	12
205/65R15	99	TXL	6J	775	340	209	647	768	12
185/65R14	86	H	51/2J	530	250	189	596	834	12
185/65R14	86	T	51/2J	530	250	189	596	834	12
175/65R14	82	T	5J	475	250	177	584	851	12
175/65R14	84	T	5J	475	250	177	584	851	12
165/70R13	79	H	6.00B	437	250	170	562	884	11
175/70R13	82	T	5J	475	300	177	576	862	12
175/70R13	82	H	5J	475	300	177	576	862	12
195/70R14	91	T	6J	615	250	201	630	789	11
185/70R14	88	T	51/2J	560	250	189	616	806	11
175/70R14	84	T	5J	500	300	177	602	825	12
175/70R14	88	TXL	5J	560	350	177	602	825	12
185/60R15	88	TXL	51/2J	560	340	189	603	824	10
185/65R15	88	H	51/2J	560	250	189	621	800	12
185/65R15	88	V	51/2J	560	250	189	621	800	12
185/65R15	88	T	51/2J	560	250	189	621	800	12
215/65R16	98	H	61/2J	750	300	221	686	724	12
205/60R16	96	HXL	6J	710	340	209	652	762	11
215/60R16	99	TXL	61/2J	775	340	221	644	771	11

LIGHT TRUCK RADIAL TIRE

D108

SIGNIFICANT FEATURES

- Super solid structural design,shock-resistant and strong wear resistant.
- Wide and enclosed-type shoulder dseign improves grip on wet road.
- Wide tire running area makes for balance road contact,giving a comfort and Endurable riding.
- Tough bead design endows tires with good cornerning and control capability on road.
- Belt plies composed of steel wires reinforce body plies and increase safety Performance.

Size	P.R	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
185R14C	6PR	Q	51/2J	725/690	350	188	652	762	10
185R14C	8PR	Q	51/2J	850/800	450	188	652	762	10
195R14C	6PR	N	51/2J	805/770	350	198	666	746	12
195R14C	8PR	N	51/2J	925/875	450	198	666	746	12
185R15C	8PR	N	51/2J	875/850	450	188	674	737	10

LIGHT TRUCK RADIAL TIRE

SW01

SIGNIFICANT FEATURES

- Specialized snow ligh truck pattern design for winter driving.
- Special rubber tread maintains effective flexibility and ensures grip under in low temperature conditions.
- Multi-sheet, multi-angular tread pattern design strengthens the anti-skid capability to ensure safe winter driving.
- Using narrow full-wrapped cap ply to enhance the high-speed satety.
- Tilizes specialized tread design to guide electric conduction channels that reduce static electricity accumulation.

Size	P.R	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
LT245/75R16	10PR	Q	7J	1400/1250	550	248	774	682	12
LT265/75R16	10PR	Q	71/2J	1550/1400	550	267	804	656	12
LT265/70R17	10PR	Q	8J	1450/1320	550	272	804	656	12

LIGHT TRUCK RADIAL TIRE
C212

SIGNIFICANT FEATURES

- Load-pattern designed for light truck;
- High wear-resistant tread compound to improve tire mileage;
- Newly designed block pattern with good grip and tear resistance;
- Has good grip in the wet ground;
- High triangular rubber sidewall designed to effectively enhance the rigidity and improve handling capability.

Size	Load. Index	Speed	P.R	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm		
155R13C	85/83	Q	6	4.50B	515/487	350	157	578	913	10
155R13C	90/88	R	8	4.50B	600/560	450	157	578	913	10
165R13C	88/89	Q	6	4.50B	615/600	350	165	594	888	10
165R13C	94/93	R	8	4.50B	670/650	450	166	595	888	10
175R13C	92/90	Q	6	5.00B	630/600	350	177	610	865	10
175R13C	97/95	R	8	5.00B	730/690	450	177	610	865	10
205R14C	102/100	Q	6	6J	850/800	350	208	684	771	10
205R14C	107/105	R	8	7J	975/925	450	209	685	771	10
195R15C	106/104	R	8	5.5J	950/900	450	196	690	765	11
195R15C	106/104	S	8	5.5J	950/900	450	196	690	765	11
215R15C	109/107	S	6	6J	1030/975	375	218	722	731	12
215R15C	109/107	T	6	6J	1030/975	375	218	722	731	12
205/70R15C	104/102	R	6	6J	900/850	350	209	669	789	11
205/70R15C	106/104	S	8	6J	950/900	450	209	669	789	11
205/70R15C	106/104	R	8	6J	950/900	450	209	669	789	11

LIGHT TRUCK RADIAL TIRE
C222

SIGNIFICANT FEATURES

- Light truck load tread design.
- Utilizes non-directional tread pattern design to improve traction.
- Variable pitch design reduces road noise and provides a more comfortable riding environment.
- Utilizes high-strength belt to enhance the impact resistant capability of tires.
- High-strength apex rubber gives tire higher stability and steering response.

Size	P.R	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load. Index	(32/Inch)
185/85R16C	\	L	5J	1090/1030	600	184	723	730	10
P235/75R15	\	H	61/2J	925	300	235	733	720	10

LIGHT TRUCK RADIAL TIRE

K323

SIGNIFICANT FEATURES

- Specialized all traffic tread design for SUV and Pickup.
- Utilizes block design with three variable pitches to help reduce tire noise.
- Utilizes high-strength belt to enhance the impact resistant capability of tires.
- Four anti-skid groove with advanced features that further enhance superiority in wet conditions.
- Specially designed wear and tear resistant tread formula provides superior driving experience.

Size	Load. Index	Speed	P.R	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
245/70R16C	107	S	6	7J	975	375	248	750	704	12
245/70R16C	107	T	6	7J	975	375	248	750	704	12
LT315/70R17	121/118	R	8	91/2J	1450/1320	350	323	874	604	12
245/75R15C	109	T	6	7J	1030	375	248	749	704	12
LT235/75R15	104/101	Q	6	61/2J	900/850	350	235	733	720	12
LT235/75R15	110/107	Q	8	61/2J	1060/975	450	235	733	720	12
LT215/75R15	106/103	Q	8	6J	950/875	450	216	703	751	12

LIGHT TRUCK RADIAL TIRE

K324

SIGNIFICANT FEATURES

- Entire traffic pattern designed for SUV,pickup.
- The use of a wide travelling surface to improve tire grip,to ensure the passage of the car.
- Using a large block pattern design to ensure the control capability under all traffic conditions.
- Special tear-resistant,wear-resistant tread compound provides superior driving experience.

Size	Load. Index	Speed	P.R	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
LT215/75R15	106/103	Q	8	6J	950/875	450	215	703	751	12
LT235/75R15	110/107	Q	8	61/2J	1060/975	450	235	733	720	12

LIGHT TRUCK RADIAL TIRE

K333

SIGNIFICANT FEATURES

- Specialized all traffic tread design for SUV and Pickup.
- Utilizes block design with three variable pitches to help reduce tire noise.
- Utilizes high-strength belt to enhance the impact resistant capability of tires.
- Four anti-skid groove with advanced features that further enhance superiority in wet conditions.
- Specially designed wear and tear resistant tread formula provides superior driving experience.

Size	Load. Index	Speed	P.R	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	RPM	(32/Inch)
LT275/55R20	117	S	/	81/2J	1285	350	282	814	648	12
LT275/55R20	117	T	/	81/2J	1285	350	282	814	648	12
LT285/65R18	125	R	/	81/2J	1650	550	292	827	638	12
LT285/65R18	121	S	/	81/2J	1450	550	292	827	638	12
LT285/70R17	126	R	10	81/2J	1700	550	292	832	634	12
LT285/70R17	126	S	8	81/2J	1700	550	292	832	634	12

TRUCK RADIAL TIRE

YTR08

SIGNIFICANT FEATURES

- Hook-like pattern block,open shoulder design,provides excellent grip,suitable for various types of trucks;
- Using high wear-resistant sidewall formulations,to avoid sidewall scratching and ensure the tire life;
- The design of deep steel sheet and based rubber can effectively improve tire grip and provide low noise.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
LT235/85R16	10	P	61/2J	850	550	235	810	102	19
LT285/75R16	10	P	8J	1700	550	295	838	126	19
LT265/75R16	10	P	71/2J	1550	550	275	808	123	19

TRUCK RADIAL TIRE

MT

SIGNIFICANT FEATURES

- Suitable for all road conditions.
- Four tortuous wide tread groove can maintain good traction in bad road conditions;
- Endow tires with good wear resistance and strong driving force.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
35X12.50R20LT	10	Q	10J	1450/3195	550	340	890	375//593	13.4
LT325/60R18	8	Q	91/2J	1360/3000	345	326	838	353/630	12.8
LT285/65R18	10	Q	81/2J	1650/3640	550	285	826	346/639	11.2
LT305/55R20	10	Q	91/2J	1450/3195	450	320	840	354/629	12.6
LT285/70R17	10	Q	81/2J	1700/3750	550	292	832	348/635	11.5
LT325/60R20	8	Q	91/2J	1450/3195	345	328	892	374/592	12.9
37X13.50R22LT	10	Q	11J	1550/3415	450	350	941	398/561	13.8
LT285/55R20	10	Q	9J	1500/3305	550	298	820	345/644	11.7
275/60R20	-	Q	8J	1180/2601	240	279	838	349/630	11.0
LT325/50R22	10	QT	10J	1500/3305	450	335	887	374/595	13.2

TRUCK RADIAL TIRE

YTR10

SIGNIFICANT FEATURES

- Suitable for all road conditions.
- Four tortuous wide tread groove can maintain good traction in bad road conditions;
- Endow tires with good wear resistance and strong driving force.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
7.00R16LT	12	N	5.50F	1215/1206	670	200	775	115/110	10.5
7.00R16LT	10	N	5.50F	1090/975	560	200	775	111/107	10.5
7.50R16LT	10	N	6.00G	1250/1090	560	215	805	116/111	10.5
7.50R16LT	12	N	6.00G	1400/1250	670	215	805	120/116	10.5
7.50R16LT	14	N	6.00G	1500/1320	770	215	805	122/118	10.5

TRUCK RADIAL TIRE

YTH1

SIGNIFICANT FEATURES

- Applicable for all road condition.
- 3 curve wide pattern slot enables the vehicle to remain fine traction and stable driving with extremely high durability.
- Superb all-over properties.
- Strong wear resistance and powerful drive force.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
7.50R16LT	12	K	6.00G	1400/1250	670	216	808	120/116	15
7.50R16LT	14	K	6.00G	1500/1320	770	216	808	122/118	15
8.25R16LT	14	K	6.50H	1700/1500	670	231	857.6	126/122	15
8.25R16LT	16	K	6.50H	1800/1600	770	231	857.6	128/124	15
8.25R20	14	K	6.5	2240/2120	830	231	974	136/134	16
8.25R20	16	K	6.5	2430/2300	930	231	974	139/137	16
9.00R20	14	K	7.0	2575/2430	790	260	1018	141/139	19
9.00R20	16	K	7.0	2800/2650	900	260	1018	144/142	19
10.00R20	16	K	7.5	3000/2725	830	276	1051	146/143	20
10.00R20	18	K	7.5	3250/3000	930	276	1051	149/146	20
11.00R20	16	K	8.0	3350/3075	830	290	1084	150/147	21
11.00R20	18	K	8.0	3550/3250	930	290	1084	152/149	21
12.00R20	18	K	8.5	3750/3450	830	312	1125	154/151	21
12.00R20	20	K	8.5	4000/3650	900	312	1125	156/153	21
12.00R24	18	K	8.5	4250/3875	830	310	1216	158/155	20
12.00R24	20	K	8.5	4500/4125	900	310	1216	160/157	20
11R22.5	14	K	8.25	2800/2650	720	286	1045	144/142	20
11R22.5	16	K	8.25	3000/2725	830	286	1058	146/143	20
315/80R22.5	18	L	9.00	3750/3450	830	308	1083	154/151	21
315/80R22.5	20	L	9.00	4000/3350	850	308	1083	156/150	21

TRUCK RADIAL TIRE

YTH2

SIGNIFICANT FEATURES

- Applicable for bus or truck cornering axle.
- Applicable for all round express way and highway service.
- Optimal handling stability and grip on wet road and easy cornering.
- Outstanding high speed performance stable road contact from wider tread design,strong wear resistance.
- Laminated tread design lowers crown heat generation under overload and prolongs tire service life

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
9.00R20	14	K	7.0	2575/2430	790	260	1018	141/139	19
9.00R20	16	K	7.0	2800/2650	900	260	1018	144/142	19
10.00R20	16	K	7.5	3000/2725	830	276	1051	146/143	21
10.00R20	18	K	7.5	3250/3000	930	276	1051	149/146	21
11.00R20	16	K	8.0	3350/3075	830	290	1084	150/147	21
11.00R20	18	K	8.0	3550/3250	930	290	1084	152/149	21
11R22.5	14	K	8.25	2800/2650	720	286	1045	144/142	21
11R22.5	16	K	8.25	3000/2725	830	286	1045	146/143	21

TRUCK RADIAL TIRE

YTH3

SIGNIFICANT FEATURES

- All round pattern applicable for highway/off-highroad service.
- Designed for cargo vehicle,self-uloading vehicle and various kinds of engineering vehicles.
- Lug and rib type pattern for super powerful driving force and durability under bad conditions.
- High level wear resistance.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
9.00R20	14	K	7.0	2575/2430	790	260	1018	141/139	19
9.00R20	16	K	7.0	2800/2650	900	260	1018	144/142	19
10.00R20	16	K	7.5	3000/2725	830	276	1051	146/143	20
10.00R20	18	K	7.5	3250/3000	930	276	1051	149/146	20
11.00R20	16	K	8.0	3350/3075	830	290	1084	150/147	21
11.00R20	18	K	8.0	3550/3250	930	290	1084	152/149	21
12.00R20	18	K	8.5	3750/3450	830	312	1125	154/151	21
12.00R20	20	K	8.5	4000/3650	900	312	1125	156/153	21

TRUCK RADIAL TIRE

YTH4

SIGNIFICANT FEATURES

- Suitable for full directional,expressway and fine condition roads.
- Grooves designed on shoulder prevent from irregular wear.
- Great anti wet and skid performance and outstanding handling property.
- Special small protrusions in grooves prevent tire from pricking and reinforce self cleaning capability.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
215/75R17.5	16	J	6.00	2180/2060	850	208	764	135/133	16
225/70R19.5	12	M	6.75	1650/1550	660	223	810	125/123	16
225/70R19.5	14	M	6.75	1800/1700	760	223	810	128/126	16
235/75R17.5	16	J	6.75	2725/2575	875	232	793	143/141	16
245/70R19.5	16	J	7.50	2180/2060	830	245	835	135/133	16
255/70R22.5	16	J	7.50	2500/2300	830	258	928	140/137	16
265/70R19.5		J	7.50	2500/2360	775	260	861	140/138	16
265/70R19.5	14	J	7.50	2300/2120	760	260	861	137/134	16
275/70R22.5	16	J	8.25	2800/2575	830	274	958	144/141	19
275/70R22.5	16	J	8.25	3150/2900	900	274	958	148/145	19
11R22.5	14	K	8.25	2800/2650	720	286	1045	144/142	19
11R22.5	16	K	8.25	3000/2725	830	286	1045	146/143	19
11R24.5	14	K	8.25	3000/2725	720	286	1092	146/143	19
11R24.5	16	K	8.25	3250/3000	830	286	1092	149/146	19
295/75R22.5	14	K	9.00	2800/2575	760	286	1019	144/141	19
295/75R22.5	16	K	9.00	3000/2725	830	286	1019	146/143	19
285/75R24.5	14	K	8.25	2800/2575	760	270.4	1047.5	144/141	19
285/75R24.5	16	K	8.25	3075/2800	830	270.4	1047.5	147/144	19

TRUCK RADIAL TIRE

YTH5

SIGNIFICANT FEATURES

- Massive shoulders pattern and central parts of vertical pattern design and open the pattern design and optimize the structure of bead belt,pattern block design of irregular shape.
- The central tread tire tread of the two countries are continuous,shoulder is wide cross channel, which combined to have better traction and brake performance,good drainage, noise reducing pavement drive.
- On driving wheels,but also showed low oil consumption and high mileage.
- Applicable to ordinary road vehicles on the driving wheel of passenger cars and trucks.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
10.00R20	16	K	7.5	3000/2725	830	278	1054	146/143	26
10.00R20	18	K	7.5	3250/3000	930	278	1054	149/146	26
11.00R20	16	K	8.0	3350/3075	830	293	1085	150/147	22
11.00R20	18	K	8.0	3550/3250	930	293	1085	152/149	22
12.00R20	18	K	8.5	3750/3450	830	315	1125	154/151	22
12.00R20	20	K	8.5	4000/3650	900	315	1125	156/153	22

TRUCK RADIAL TIRE

YTH6

SIGNIFICANT FEATURES

- Highly wear resistant deeper pattern for greater mileage.
- Combination of bars and blocks,closed tire shoulder figure,provide super driving and durability under bad conditions.
- Special small protrusions in grooves prevent tire from pricking and reinforce self-cleaning capability.
- Enhanced embossing,longer driving distance.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
11R22.5	14	K	8.25	2800/2650	720	286	1058	144/142	27
11R22.5	16	K	8.25	3000/2725	830	286	1058	146/143	27
11R24.5	14	K	8.25	3000/2725	720	286	1105	146/143	27
11R24.5	16	K	8.25	3250/3000	830	286	1105	149/146	27
295/75R22.5	14	K	9.00	2800/2575	760	286	1032	144/141	27
295/75R22.5	16	K	9.00	3000/2725	830	286	1032	146/143	27
285/75R24.5	14	K	8.25	2800/2575	760	270	1060	144/141	27
285/75R24.5	16	K	8.25	3075/2800	830	270	1060	147/144	27

TRUCK RADIAL TIRE

YTH7

SIGNIFICANT FEATURES

- Applicable for high speed driving Best choice for deluxe bus.
- Endow tires with superior stability of centerline road contact driving.
- Low noise level,reduce slip of tire,low rolling resistance.
- Greatly reduce tire irregular wear.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
295/80R22.5	16	L	9.00	3350/3075	830	292	1046	150/147	18
295/80R22.5	18	L	9.00	3550/3250	900	292	1046	152/149	18
315/80R22.5	18	L	9.00	3750/3450	830	308	1076	154/151	18
315/80R22.5	20	L	9.00	4000/3350	850	308	1076	156/150	18
12R22.5	16	L	9.00	3350/3075	830	292	1083	150/147	18
12R22.5	18	L	9.00	3550/3250	930	292	1083	152/149	18
13R22.5	16	K	9.75	3550/3250	760	320	1122	152/149	19
13R22.5		K	9.75	4000/3350	875	320	1122	156/150	19

TRUCK RADIAL TIRE

YTH8

SIGNIFICANT FEATURES

- Bridged center design helps improve tread stability.
- High density of grooves help provide excellent traction in all weather conditions.
- Directional tread design allows for good traction and long original tread life.
- Blocks,opened tire shoulder figure,thus enabling the tire to achieve super performance in operation under bad conditions.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
295/80R22.5	16	L	9.00	3350/3075	830	292	1046	150/147	27
295/80R22.5	18	L	9.00	3550/3250	900	292	1046	152/149	27
315/80R22.5	18	L	9.00	3750/3450	830	308	1083	154/151	28
315/80R22.5	20	L	9.00	4000/3350	850	308	1083	156/150	28
12R22.5	14	L	9.00	3350/3075	830	292	1083	150/147	27
12R22.5	16	L	9.00	3550/3250	930	292	1083	152/149	27
13R22.5	14	K	9.75	3550/3250	760	320	1122	152/149	29
13R22.5	16	K	9.75	4000/3350	875	320	1122	156/150	29
11R22.5	14	K	8.25	2800/2650	720	286	1053	144/142	29
11R22.5	16	K	8.25	3000/2725	830	286	1053	146/143	29
11.00R20	16	K	8.00	3350/3075	830	293	1085	150/147	27
11.00R20	18	K	8.00	3550/3250	930	293	1085	152/149	27

TRUCK RADIAL TIRE

YTH9

SIGNIFICANT FEATURES

- Special tread adhesive,tear and puncture.
- Resistance and extra-deep tread pattern improving.
- It's special for field engineering vehicles rode on Stone pit,work site and sand-covered roads.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
10.00R20	16	K	7.5	3000/2725	830	278	1054	146/143	29
10.00R20	18	K	7.5	3250/3000	930	278	1054	149/146	29
11.00R20	16	K	8.0	3350/3075	830	293	1085	150/147	29
11.00R20	18	K	8.0	3550/3250	930	293	1085	152/149	29
12.00R20	18	K	8.5	3750/3450	830	315	1125	154/151	27
12.00R20	20	K	8.5	4000/3650	900	315	1125	156/153	27

TRUCK RADIAL TIRE

YTH10

SIGNIFICANT FEATURES

- Vertical pattern,suitable for high speed.
- Continuous shoulder to prevent irregular wear.
- Longitudinal furrow and fine knives in the direction of multi-slot design and make it with excellent heat dissipation and control.
- Special design prevents the gully base of tread groove cracking, but can also prevent clip stones with a good self-cleaning and lowering noise performance.
- On steering axis shows excellent durability,long service life and low fuel consumption performance.
- Apply a good road running bus and a van truck steering wheel and tug boat

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
385/65R22.5	18	K	11.75	4250	830	397	1069	158	20
385/65R22.5	20	K	11.75	4500	900	397	1069	160	20

TRUCK RADIAL TIRE

YTH12

SIGNIFICANT FEATURES

- Vertical pattern,suitable for high speed.
- Continuous shoulder to prevent irregular wear.
- Longitudinal furrow and fine knives in the direction of multi-slot design and make it with excellent heat dissipation and control.
- Design and reducing noise performance of treachery moment.
- On steering axis shows excellent durability,long service life and low fuel consumption performance.
- Apply a good road running bus and a van truck steering wheel and tug boat

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
12R22.5	16	L	9.00	3350/3075	830	292	1083	150/147	20
12R22.5	18	L	9.00	3550/3250	930	292	1083	152/149	20

TRUCK RADIAL TIRE

YTH13

SIGNIFICANT FEATURES

- Four vertical pattern, so that it has a higher handling stability, suitable for high speed
- Continuous shoulder to prevent irregular wear.
- Longitudinal furrow and fine knives in the direction of multi-slot design and make it with excellent heat dissipation and control.
- Design and reducing noise performance of treachery moment.
- Special design prevents the gully base of tread groove cracking, but can also prevent clip stones with a good self-cleaning and lowering noise performance.
- Apply a good road running bus and a van truck steering wheel and tug boat

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
12R22.5	16	L	9.00	3350/3075	830	292	1083	150/147	20
12R22.5	18	L	9.00	3550/3250	930	292	1083	152/149	20

TRUCK RADIAL TIRE

YTH15

SIGNIFICANT FEATURES

- Vertical pattern, suitable for high speed.

  Continuous shoulder to prevent irregular wear.

  Longitudinal furrow and fine knives in the direction of multi - slot design and make it with excellent heat dissipation and control.

  Design and reducing noise performance of treachery moment.
- On steering axis shows excellent durability, long service life and low fuel consumption performance.
-
- Apply a good road running bus and a van truck steering wheel and tug boat.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
11R22.5	14	K	8.25	2800/2650	720	286	1053	144/142	19
11R22.5	16	K	8.25	3000/2725	830	286	1053	146/143	19

TRUCK RADIAL TIRE

YTH16

SIGNIFICANT FEATURES

- Four vertical pattern, so that it has a higher handling stability, suitable for high speed
- Continuous shoulder to prevent irregular wear.
- Longitudinal furrow and fine knives in the direction of multi-slot design and make it with excellent heat dissipation and control.
- Design and reducing noise performance of treachery moment.
- Special design prevents the gully base of tread groove cracking, but can also prevent clip stones with a good self-cleaning and lowering noise performance.
- Apply a good road running bus and a van truck steering wheel and tug boat

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
12R22.5	16	L	9.00	3350/3075	830	292	1083	150/147	23
12R22.5	18	L	9.00	3550/3250	930	292	1083	152/149	23

TRUCK RADIAL TIRE

YT901

SIGNIFICANT FEATURES

- Special deep pattern edsign and create a good road braking effect, reducing irregular wear, increasing fuel usage.
- Transverse pattern groove design, Strengthening cross country running and controlling performance and shoulders pattern design of special treatment, can quickly eliminate heat accumulation with high wear resistance and durability.
- Suitable for poor bumpy road, tractors, ordinary goods vehicle, Tipper and driving wheel use of concrete mixing truck tire tread.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
7.00R16LT	10	L	5.50F	1090/975	560	200	775	111/107	15
7.00R16LT	12	L	5.50F	1215/1060	670	200	775	115/110	15
7.50R16LT	12	K	6.00G	1400/1250	670	216	808	120/116	19
7.50R16LT	14	K	6.00G	1500/1320	770	216	808	122/118	19
8.25R16LT	14	K	6.50H	1700/1500	670	231	857.6	126/122	19
8.25R16LT	16	K	6.50H	1800/1600	770	231	857.6	128/124	19
8.25R20	14	K	6.5	2240/2120	830	231	974	136/134	19
8.25R20	16	K	6.5	2430/2300	930	231	974	139/137	19
9.00R20	14	K	7.0	2575/2430	790	260	1018	141/139	21
9.00R20	16	K	7.0	2800/2650	900	260	1018	144/142	21
10.00R20	16	K	7.5	3000/2725	830	276	1051	146/143	21
10.00R20	18	K	7.5	3250/3000	930	276	1051	149/146	21
11.00R20	16	K	8.0	3350/3075	830	290	1084	150/147	21
11.00R20	18	K	8.0	3550/3250	930	290	1084	152/149	21
12.00R20	18	K	8.5	3750/3450	830	312	1125	154/151	22
12.00R20	20	K	8.5	4000/3650	900	312	1125	156/153	22

TRUCK RADIAL TIRE

YT902

SIGNIFICANT FEATURES

- Patterns and deep tread pattern groove Design of Mixing and massive, with good tractive and braking performance.
- Matrix using super structure, with excellent bearing capacity of super wear.
- Resistant and anti into the ligation of tread formula applies to poor condition of roads.
- Suitable for poor bumpy road, tractors, ordinary goods vehicle, Tipper and driving wheel use of concrete mixing truck tire tread.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
11.00R20	16	K	8.0	3350/3075	830	293	1085	150/147	24
11.00R20	18	K	8.0	3550/3250	930	293	1085	152/149	24
12.00R20	18	K	8.5	3750/3450	830	315	1120	154/151	26
12.00R20	20	K	8.5	4000/3650	900	315	1120	156/153	26

TRUCK RADIAL TIRE

YT903

SIGNIFICANT FEATURES

- The transverse pattern block design effective control on noise and drainage of ARC trench to tire, self - cleaning capability. Good braking, driving capability.
- Excellent wear resistance of tread formula of improving tire, anti - pricking their performance.
- Suitable for poor bumpy road, tractors, ordinary goods vehicle, Tipper and driving wheel use of concrete mixing truck tire tread.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
11.00R20	16	K	8.0	3350/3075	830	293	1085	150/147	24
11.00R20	18	K	8.0	3550/3250	930	293	1085	152/149	24
12.00R20	18	K	8.5	3750/3450	830	315	1120	154/151	25
12.00R20	20	K	8.5	4000/3650	900	315	1120	156/153	25

TRUCK RADIAL TIRE

YT905

SIGNIFICANT FEATURES

- Patterns and deep tread pattern groove Design of Mixing and massive, with good tractive and braking performance.
- Matrix using super structure, with excellent bearing capacity of super wear.
- Resistant and anti into the ligation of tread formula applies to poor condition of roads.
- Suitable for poor bumpy road, tractors, ordinary goods vehicle, Tipper and driving wheel use of concrete mixing truck tire tread.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
11.00R20	16	K	8.0	3350/3075	830	293	1085	150/147	24
11.00R20	18	K	8.0	3550/3250	930	293	1085	152/149	24
12.00R20	18	K	8.5	3750/3450	830	315	1120	154/151	24
12.00R20	20	K	8.5	4000/3650	900	315	1120	156/153	24

TRUCK RADIAL TIRE

YT906

SIGNIFICANT FEATURES

- Patterns and deep tread pattern groove Design of Mixing and massive, with good tractive and braking performance.
- Matrix using super structure, with excellent bearing capacity of super wear.
- Resistant and anti into the ligation of tread formula applies to poor condition of roads.
- Suitable for poor bumpy road, tractors, ordinary goods vehicle, Tipper and driving wheel use of concrete mixing truck tire tread.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
10.00R20	16	J	7.5	3000/2725	830	278	1054	146/143	32.8
10.00R20	18	J	7.5	3250/3000	930	278	1054	149/146	32.8
11.00R20	16	J	8.0	3350/3075	830	293	1085	150/147	32.8
11.00R20	18	J	8.0	3550/3250	930	293	1085	152/149	32.8
12.00R20	18	J	8.5	3750/3450	830	315	1125	154/151	32.8
12.00R20	20	J	8.5	4000/3650	900	315	1125	156/153	32.8

TRUCK RADIAL TIRE

YT101

SIGNIFICANT FEATURES

- Mixed pattern of longitudinal and transverse patterns into, the patterns on width, patterns of saturation of high wear resistance and brake good, strong adaptability.
- Rational shoulder groove and heat.

  Shoulder part of the continuous, ensure the stability of the well, easily move and shoulder different grinding.
- Bottom rubber blocks are effective in preventing groove bottom crack of outstanding.

  Shoulder small pattern groove design, reduce noise and better heat dissipation performance, driving comfort, driving safer.
- For bus driving in all kinds of good roads of whole wheel tread, long - distance, high - speed, wear - resisting.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
10.00R20	16	K	7.5	3000/2725	830	276	1051	146/143	19
10.00R20	18	K	7.5	3250/3000	930	276	1051	149/146	19
11.00R20	16	K	8.0	3350/3075	830	290	1084	150/147	19
11.00R20	18	K	8.0	3550/3250	930	290	1084	152/149	19
12.00R20	18	K	8.5	3750/3450	830	312	1125	154/151	19
12.00R20	20	K	8.5	4000/3650	900	312	1125	156/153	19

DURUN·盾轮®

TRUCK RADIAL TIRE

YT102

SIGNIFICANT FEATURES

- Vertical pattern, suitable for high speed.
- Continuous shoulder to prevent irregular wear.
- Wide tread improve adhesion of tire - ground.
- Circumferential Steel tire Thermal performance can be increased, irregular pitch designed to reduce noise pollution, improving riding comfort.
- Apply card and Buses driving through a variety of whole wheel tread of good roads, long - distance, high - speed, wear - resisting.

Size	PR	Speed	Rim	Max.Load Kg	Pressure kPa	S.W. mm	O.Dia mm	Load.Index	(32/Inch)
7.00R16LT	10	L	5.50F	1090/975	560	200	775	111/107	15
7.00R16LT	12	L	5.50F	1215/1060	670	200	775	115/110	15
7.50R20	12	L	6.0	1800/1700	760	215	935	128/126	16
7.50R20	14	L	6.0	1900/1800	830	215	935	130/128	16
6.50R16LT	10	L	5.50F	975/850	560	185	750	107/102	14
6.50R16LT	12	L	5.50F	1060/925	670	185	750	110/105	14

Memorandum