

Double Coin RR300 (CMA) Premium All Position w/Decoupling Groove

- Four decoupling grooves to equalize weight distribution reducing irregular wear
- Rock ejector base prevents stone drilling and stone retention to improve casing retreadability and durability
- Designed for steer application



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61291255	11R22.5 143/139M	14	113.7	8.25	41.4	11.1	19/32
61291256	11R22.5 148/145M	16	116.9	8.25	41.4	11.1	19/32
61299255	295/75R22.5 144/141M	14	116.5	9.00	40.6	11.7	19/32
61291455	11R24.5 145/141M	14	116.3	8.25	43.1	10.9	19/32
61291456	11R24.5 149/145M	16	126.3	8.25	43.3	10.9	19/32
61298455	285/75R24.5 144/141M	14	117.6	8.25	41.6	12.2	19/32

Double Coin RR200L (CMA) Premium All Position w/Decoupling Groove

- Extra deep tread design for on and off road applications
- Chip and cut resistant compound to avoid snags and tears
- Reinforced all-steel construction with four full steel cap plies to protect against punctures and impact breaks



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
3311258	315/80R22.5 157/154K	20	141.5	9.00	42.5	12.0	20/32

Double Coin RR400 (CMA) Premium All Position Highway

- Premium tread depth for long mileage
- Wide shoulder to prevent snags, tears and uneven wear
- Four steel belts for toughness, uniform wear and stability



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
3369205	9.00R20 141/136L	14	102.5	7.00	40.2	10.1	19/32
3360225	10R22.5 141/136L	14	106.3	7.00	40.2	10.0	19/32

Double Coin RR800 (CMA)

4-Rib All Position Highway

- Premium tread depth for long life
- Wide shoulder to prevent snags, tears and uneven wear
- Four steel belts for toughness, uniform wear and stability



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61289214	9R22.5 136/134L	14	110.0	6.75	38.3	9.1	17/32

Double Coin RR150 (CMA)

Premium All Position 5-Rib Highway

- Special tread design to reduce irregular wear
- Improved contour for outstanding strength, durability and retreadability
- Shoulder designed to minimize shoulder cracking and step wear



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61281026	1000R20 148/144L	16	111.4	7.50	41.3	10.7	19/32
61232855	11R22.5 143/139M	14	113.7	8.25	41.4	11.1	19/32
3281256	11R22.5 148/145M	16	116.9	8.25	41.4	11.1	19/32
61289255	295/75R22.5 144/141M	14	116.5	9.00	40.6	11.7	19/32
61268145	11R24.5 145/141L	14	116.3	8.25	43.3	10.9	19/32
3281456	11R24.5 149/145L	16	126.3	8.25	43.3	10.9	19/32
61268845	285/75R24.5 144/141M	14	117.6	8.25	41.5	11.0	19/32

Double Coin RT606+ (CMA)

Premium All Position 5-Rib Regional Steer

- Special tread design to reduce irregular wear
- Improved contour for outstanding strength, durability and retreadability
- Shoulder designed to minimize shoulder cracking and step wear



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61267125	11R22.5 144/142L	14	127.6	8.25	41.6	11.1	22/32
61260256	11R22.5 146/143L	16	127.6	8.25	41.6	11.1	22/32
61260255	295/75R22.5 144/141L	14	132.5	9.00	40.7	11.7	22/32
61260455	11R24.5 146/143L	14	137.5	8.25	43.5	10.9	22/32
61260456	11R24.5 149/146L	16	137.5	8.25	43.5	10.9	22/32
61260055	285/75R24.5 144/141L	14	133.9	8.25	41.5	10.6	22/32

Double Coin RT500 (CMA) Premium All Position Low Profile Highway

- Specially designed for steer axles and all position usage
- 5-rib tread design for premium handling and long life tread
- Four steel belts for toughness, uniform wear and stability



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
2598257	825R15 143/141J	18	49.0	6.50	33.2	9.1	16/32
61291057	1000R15 148/145J	18	82.0	7.50	36.3	10.8	16/32
61297565	750R16 122/118J	14	51.9	6.50	31.7	8.3	16/32
61291783	8R175 117/116L	10	49.0	6.00	30.9	8.2	16/32
3391776	215/75R17.5 135/133J	16	61.3	6.00	30.4	8.5	16/32
61256795	235/75R17.5 143/141J	16	68.1	6.75	31.6	9.2	16/32
3391706	10R175 143/141J	16	70.0	7.50	33.9	9.8	16/32
3392795	225/70R19.5 125/123J	12	68.1	6.75	32.3	8.2	16/32
3394796	245/70R19.5 141/140J	16	77.3	7.50	33.2	9.6	16/32
3390894	8R19.5 124/122J	12	56.7	6.00	34.1	8.2	16/32
3396796	265/70R19.5 143/141J	16	88.7	7.50	34.3	10.0	16/32
61265726	255/70R22.5 140/137N	16	84.2	7.50	36.6	10.0	16/32
3397726	275/70R22.5 148/145M	16	104.0	8.25	37.8	10.6	16/32

Double Coin RLB1 (CMA) Open Shoulder Drive

- Extra deep tread for long mileage and improved traction
- Full depth siping provides excellent traction throughout the life of the tread
- Four steel belts for toughness, uniform wear and stability



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61211026	10.00R20 148/144J	16	124.0	7.50	41.5	10.7	22/32
3411255	11R22.5 143/139M	14	123.5	8.25	41.7	10.9	26/32
3411256	11R22.5/16 148/145M	16	125.3	8.25	41.7	10.9	26/32
3419255	295/75R22.5 144/141M	14	118.5	9.00	40.9	11.7	26/32
3411455	11R24.5 145/141L	14	131.8	8.25	43.7	10.9	26/32
61261145	11R24.5 149/145L	16	134.3	8.25	43.7	10.9	26/32
3418455	285/75R24.5 144/141L	14	126.9	8.25	41.4	11.0	26/32

Double Coin RLB400 (CMA) Premium Closed Shoulder Drive

- Premium tread depth for long mileage
- Wide shoulder to prevent snags, tears and uneven wear
- Four steel belts for toughness, uniform wear and stability



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
3481255	11R22.5 143/139J	14	123.5	8.25	42.0	10.9	30/32
3481256	11R22.5 148/145J	16	125.3	8.25	42.0	10.9	30/32
61234855	295/75R22.5 144/141J	14	118.5	9.00	41.2	11.7	30/32
61281455	11R24.5 145/141J	14	131.8	8.25	43.9	10.9	30/32
3481456	11R24.5 149/145J	16	134.3	8.25	43.9	10.9	30/32
3488455	285/75R24.5 144/141J	14	126.9	8.25	42.1	11.0	30/32

Double Coin RLB450 (CMA)

Premium Open Shoulder Drive

- Designed for toughness and durability
- 6-rib extra wide tread surface
- Four steel belts resist impact breaks, cuts and tears for added strength and durability



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61211255	11R22.5 143/137M	14	123.5	8.25	41.9	12.9	26/32
61211256	11R22.5 148/145M	16	125.3	8.25	41.9	12.9	26/32
61219255	295/75R22.5 144/141M	14	119.0	9.00	40.8	11.7	26/32
61211258	315/80R22.5 156/150L	20	141.5	9.00	43.2	12.5	29/32
61211455	11R24.5 143/139M	14	131.8	8.25	41.7	10.9	26/32
61211456	11R24.5 148/145M	16	134.3	8.25	41.7	10.9	26/32

Double Coin RLB490 (CMA)

Regional Low Profile Drive

- Tread design for on and off road usage
- Large tread elements give improved handling and excellent traction
- Four steel belts for toughness, uniform wear and stability



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61262795	225/70R19.5 125/123J	12	68.1	6.75	32.6	8.8	19/32
61260479	245/70R19.5 141/140J	16	77.3	7.50	33.5	9.6	19/32
61266796	265/70R19.5 143/141J	16	88.0	7.50	34.6	10.0	22/32
61260572	255/70R22.5 140/137J	16	94.0	7.50	37.0	10.0	22/32
61267726	275/70R22.5 148/145J	16	109.0	8.25	38.1	11.0	22/32

Double Coin TR100 (CMA)

All Position Trailer - Shallow Tread

- Designed for trailers, tag axles, as well as steer axle use
- Tread design resists irregular wear in free rolling wheel position
- 14/32" tread depth for more mileage and improved wear



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61281255	11R22.5 143/139M	14	106.5	8.25	41.0	10.9	14/32
61262550	295/75R22.5 144/141M	14	107.5	9.00	39.8	11.5	14/32
61264550	11R24.5 145/141L	14	114.5	8.25	42.7	11.3	14/32
61265500	285/75R24.5 144/141J	14	114.5	8.25	40.9	11.3	14/32

Double Coin RLB900+ (CMA)

On/Off Road All Position Traction

- Tread design for on and off road usage
- Large tread elements give improved handling and excellent traction
- Four steel belts for toughness, uniform wear and stability



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61266482	385/65R22.5 160/158K	20	160.6	11.75	42.2	14.8	22/32
61242258	425/65R22.5 165K	20	190.7	13.00	44.6	16.3	22/32
61242548	445/65R22.5 168J	20	191.0	14.00	45.3	17.9	22/32

Double Coin RR900 (CMA)

All Position Mixed Service Rib

- Tread designed for on and off road usage
- Excellent for free rolling applications
- Reduced road noise in highway use but resists off-road cuts and tears
- Four steel belts for toughness, uniform wear and stability



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61263782	385/65R22.5 160/158K	20	160.6	11.75	42.1	14.8	20/32

Double Coin RR202 (CMA)

5-Rib Highway Service Tire

- Modern multi-rib tread design excellent for free rolling applications
- 10,000lb load carrying capacity for heavy load applications
- Durable casing provides long original tread life and promotes multiple retreads



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61266622	12R22.5	18	137	9.0	42.7	11.8	19/32
61266692	295/80R22.5 154/150M	18	131	9.0	41.3	11.9	19/32
61261259	315/80R22.5 160/157	22	147	9.0	42.4	12.2	20/32

Double Coin RR99 (CMA)

Heavy Duty All Position On/Off Highway

- Strong 4-rib design for on and off highway use
- Tread design to reduce road noise in highway use but resists off-highway cuts and tears
- Reinforced all steel construction with four full steel cap plies to protect against punctures and impact breaks



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61299125	11R22.5 148/145L	16	125.3	8.25	41.3	10.9	18/32
61269922	12R22.5 152/148L	18	137.3	9.00	42.7	11.8	21/32
61239912	315/80R22.5 160/157J	22	141.5	9.00	42.4	12.2	20/32
61263227	13R22.5 154/150M	18	130.0	9.75	43.9	12.2	20/32
61299145	11R24.5 149/146L	16	134.3	8.25	43.4	10.9	21/32
3439205	900R20 141/136L	14	106.0	7.00	40.2	10.1	19/32
3431026	1000R20 148/144L	16	124.0	7.50	41.2	10.7	20/32
3431206	1100R20 149/145L	16	132.7	8.00	42.8	11.3	20/32
3432207	1200R20 154/149L	18	143.2	8.50	43.8	12.0	20/32

Double Coin RLB800 (CMA)

Premium On/Off Road Drive

- Chip, cut and abrasion resistant tread compound
- Four steel belts to resist cuts, impact breaks and tears
- Excellent traction for severe off highway use



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
61201026	10.00R20 148/144G	16	125.6	7.50	41.9	10.7	29/32
3501256	11R22.5 148/145G	16	125.3	8.25	41.9	10.9	29/32
3501456	11R24.5 149/145G	16	134.3	8.25	43.9	10.9	29/32
61262500	12.00R24 15/153K	18	221.0	8.50	48.0	12.1	29/32

Double Coin RM4 (CMA)

Heavy Duty Highway

- Premium Heavy Duty Highway Service



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
3462247	12.00R24 158/153K	18	221.0	8.50	48.0	12.0	21/32

Double Coin RR4 (CMA)

All Position On/Off Highway

- Strong 4-rib design for on and off highway use
- Tread designed to reduce road noise in highway use but resists off-highway cuts and tears
- Reinforced all-steel construction with four full steel cap plies to protect against punctures and impact breaks



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
3402247	12.00R24 158/153K	18	175.2	8.50	48.0	12.0	21/32

Double Coin RLB600 (CMA)

On/Off Road - Mining & Logging

- Extra deep tread design for on and off road applications
- Chip and cut resistant compound to avoid snags and tears
- Reinforced all-steel construction with four full steel cap plies to protect against punctures and impact breaks



Product Code	Size & Service Description	Ply Rating	WT	Rim	OD	Section Width	Tread Depth
3491256	11R22.5 148/145G	16	125.3	8.25	43.0	11.1	33/32
3491456	11R24.5 149/145G	16	134.3	8.25	44.1	11.1	33/32