



2012

THE SMART MONEY IS ON



**TRUCK TIRE DATA
AND REFERENCE BOOK**



**TABLE OF
CONTENTS**

- 1 FUEL EFFICIENT TIRES**
- 4 STEER TIRES**
- 11 TRAILER TIRES**
- 13 DRIVE TIRES**
- 18 MIXED SERVICE TIRES**
- 24 LIMITED WARRANTY**



FUEL
EFFICIENT

FR605**

ULTRA PREMIUM FUEL EFFICIENT STEER-POSITION TIRE



FEATURES & BENEFITS

- Advanced tread compounds, design and internal construction provide low rolling resistance and longer mileage
- 5-rib tread design enhances even wear, traction in long haul steer axle positions
- Features extensive siping and side-shoulder decoupling groove to enhance even wear, traction in long haul steer axle positions

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD PER RADIUS	REVS PER MILE	WEIGHT
11R22.5	14	M	41.4	11.1	17	8.25	19.8	496	113
11R22.5	16	M	41.4	11.1	17	8.25	19.8	496	117
295/75R22.5	14	M	40.6	11.7	17	9.00	18.8	510	108
11R24.5	14	M	43.3	10.9	17	8.25	20.8	473	125
11R24.5	16	M	43.3	10.9	17	8.25	20.8	473	128
285/75R24.5	14	M	41.5	11.0	17	8.25	19.5	492	124

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

** Double Coin manufactures EPA SmartWay® verified technologies

FUEL
EFFICIENT

FD405**

ULTRA PREMIUM FUEL EFFICIENT
DRIVE POSITION TIRE



FEATURES & BENEFITS

- Advanced tread compounds and internal construction provides low rolling resistance and longer mileage
- Closed-shoulder tread design provides even wear while maintaining excellent traction
- Deep $26\frac{3}{32}$ " tread with stone drilling protectors promotes long original mileage

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD PER RADIUS	REVS PER MILE	WEIGHT
11R22.5	14	L	42.0	10.9	26	8.25	20.1	488	120
11R22.5	16	L	42.0	10.9	26	8.25	20.1	488	126
295/75R22.5	14	J	41.2	11.7	26	9.00	19.0	507	120
11R24.5	14	J	43.9	10.9	26	8.25	21.1	466	135
11R24.5	16	J	43.9	10.9	26	8.25	21.1	466	138
285/75R24.5	14	J	42.1	11.0	26	8.25	19.8	485	134

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

** Double Coin manufactures EPA SmartWay® verified technologies

FUEL
EFFICIENT

FT105**

ULTRA PREMIUM FUEL EFFICIENT
TRAILER-POSITION TIRE

FEATURES & BENEFITS

- Advanced tread compounds and internal construction provides low rolling resistance and longer mileage
- Extensive tread siping helps fight irregular wear in free rolling positions
- Durable casing provides long original tread life and promotes multiple retreads

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD PER RADIUS	REVS PER MILE	WEIGHT
11R22.5	14	M	41.0	10.9	12	8.25	19.5	500	108
11R22.5	16	M	41.0	10.9	12	8.25	19.5	500	**
295/75R22.5	14	M	40.2	11.7	12	9.00	18.9	510	102
11R24.5	14	L	42.9	10.9	12	8.25	20.8	476	**
11R24.5	16	L	42.9	10.9	12	8.25	20.8	476	**
285/75R24.5	14	L	41.1	11.0	12	8.25	19.3	505	**

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

** Double Coin manufactures EPA SmartWay® verified technologies

STEER

RT606+

ULTRA PREMIUM 5-RIB REGIONAL
STEER AND ALL-POSITION TIRE



FEATURES & BENEFITS

- Enhanced tread compounds and siping fight irregular wear and provides long life in regional and all-position applications
- Premium 5-rib tread design with wide shoulders enhances durability and even wear
- Extra deep $2\frac{2}{32}$ " original tread depth allows for longer wear in regional high scrub applications

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
11R22.5	14	L	41.6	11.1	22	8.25	19.8	496	122
11R22.5	16	L	41.6	11.1	22	8.25	19.8	496	125
295/75R22.5	14	L	40.7	11.7	22	9.00	19.5	496	129
11R24.5	14	L	43.5	10.9	22	8.25	20.8	473	137
11R24.5	16	L	43.5	10.9	22	8.25	20.8	473	138
285/75R24.5	14	L	41.5	10.6	22	8.25	19.5	492	131

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

STEER

RR680

PREMIUM REGIONAL AND ALL-POSITION STEER TIRE



FEATURES & BENEFITS

- Premium 5-rib tread design with wide shoulders provides for durability and even wear in steer and all-position applications
- Deep $1\frac{9}{32}$ " original tread depth provides long original tread life
- Enhanced channel siping and wide grooves allows for premium wet and dry traction

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
9R22.5	14	L	38.3	9.1	18	6.75	17.9	206	110
11R22.5	14	L	41.4	11.1	20	8.25	19.8	499	115
11R22.5	16	L	41.4	11.1	20	8.25	19.8	499	118
295/75R22.5	14	M	40.6	11.7	20	9.00	19.5	504	118
11R24.5	14	L	43.3	10.9	20	8.25	20.8	476	129
11R24.5	16	L	43.3	10.9	20	8.25	20.8	476	132
285/75R24.5	14	L	41.5	11.0	20	8.25	19.5	492	124
295/80R22.5	16	M	41.3	11.9	18	9.00	19.8	191	120
315/80R22.5	20	L	42.4	12.2	18	9.00	19.9	188	142
305/75R24.5	16	M	42.7	11.6	19	9.00	TBA	TBA	145

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

STEER

RT600

PREMIUM LOW PROFILE REGIONAL AND ALL-POSITION STEER TIRE



FEATURES & BENEFITS

- Enhanced tread compounds and siping fight irregular wear and provides long life in regional and all-position applications
- Premium 5-rib tread design with wide shoulders provides for durability and even wear
- Durable casing provides long original tread life and promotes multiple retreads

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
225/70R19.5	12	M	32.3	8.2	16.0	6.75	15.2	635	69
245/70R19.5	16	J	33.3	9.5	16.0	7.50	15.8	610	81
265/70R19.5	16	J	34.3	10	16.0	7.50	15.9	606	86
9R22.5	14	L	38.3	9.1	18.3	6.75	17.9	206	104
8R19.5	12	M	34.1	8.2	16.0	6.00	16.3	592	68
10R22.5	14	L	40.2	10	18.0	7.50	18.9	510	108
275/70R22.5	16	J	37.9	11	18.0	8.25	17.7	543	104

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

STEER

RR150

PREMIUM 5-RIB STEER AND ALL-POSITION MULTI-USE TIRE



FEATURES & BENEFITS

- Premium 5-rib tread design with wide shoulders provides for durability and even wear in steer and all-position applications
- Deep $1\frac{9}{32}$ " original tread depth provides long original tread life
- Enhanced channel siping and wide grooves allow for premium wet and dry traction

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
11R22.5	14	M	41.4	11.1	19	8.25	19.8	499	115
11R22.5	16	M	41.4	11.1	19	8.25	19.8	499	118
295/75R22.5	14	M	40.6	11.7	19	9.00	19.5	504	118
11R24.5	14	L	43.3	10.9	19	8.25	20.8	476	129
11R24.5	16	L	43.3	10.9	19	8.25	20.8	476	132
285/75R24.5	14	M	41.5	11.0	19	8.25	19.5	492	124
10.00R20	16	L	41.3	10.7	19	7.50	19.4	497	121

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

STEER

RR300

ULTRA PREMIUM LONG HAUL
STEER-POSITION TIRE



FEATURES & BENEFITS

- 5-rib tread design with special compounds enhances even wear, traction in long haul steer axle positions
- Platform rock ejectors prevent stone drilling and stone retention to improve casing retreadability and durability
- Features multiple sipes, shoulder decoupling grooves to enhance even wear, traction in long haul steer axle positions

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
11R22.5	14	M	41.4	11.1	19	8.25	19.8	496	113
11R22.5	16	M	41.4	11.1	19	8.25	19.8	496	117
295/75R22.5	14	M	40.6	11.7	19	9.00	19.5	504	118
11R24.5	14	M	43.3	10.9	19	8.25	20.8	473	126
11R24.5	16	M	43.3	10.9	19	8.25	20.8	473	129
285/75R24.5	14	M	41.5	11.0	19	8.25	19.5	492	123
295/80R22.5	16	M	41.6	12.2	19	9.00	20.2	493	120
295/80R22.5	18	M	41.6	12.2	19	9.00	20.2	493	120

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

STEER

RR400

PREMIUM STEER AND ALL-POSITION
MULTI-USE TIRE



FEATURES & BENEFITS

- Premium $19/32$ " original tread depth for long mileage
- Wide shoulders promote even wear and excellent traction
- Durable casing promotes multiple retreads

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
9.00R20	14	L	40.2	10.1	19	7.0	18.9	511	109
9.00R20	16	K	40.2	10.1	19	7.0	18.9	511	109
10R22.5	14	M	40.2	10.0	19	7.5	18.9	510	108
10R22.5	16	M	40.2	10.0	19	7.5	18.9	510	108

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

STEER

RR200L

PREMIUM 5-RIB
HIGHWAY SERVICE TIRE



FEATURES & BENEFITS

- Deep $20/32$ " original tread for optimum use in highway applications
- Abrasion-resistant tread compound enhances original tread life
- Durable casing promotes multiple retreads

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
315/80R22.5	18	M	42.5	12.2	20	9	19.9	485	141
315/80R22.5	20	K	42.5	12.2	20	9	19.9	485	147

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

TRAILER

TR100

ULTRA PREMIUM SHALLOW TREAD TRAILER-POSITION TIRE



FEATURES & BENEFITS

- Optimum tread design promotes even wear in free rolling and trailer axle positions
- Premium $1\frac{4}{32}$ " tread depth for long original mileage
- Center rib stone platform ejectors preserve casing integrity

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
11R22.5	14	M	41.0	10.9	14	8.25	19.5	500	113
11R22.5	16	M	41.0	10.9	14	8.25	19.5	500	116
295/75R22.5	14	M	40.2	11.7	14	9.00	18.9	510	114
11R24.5	14	L	42.9	10.9	14	8.25	20.8	476	124
11R24.5	16	L	42.9	10.9	14	8.25	20.8	476	125
285/75R24.5	14	J	41.1	11.0	14	8.25	19.3	505	11

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

TRAILER

RT500

PREMIUM LOW PROFILE
ALL-POSITION MULTI-USE TIRE



FEATURES & BENEFITS

- Special tread compounds designed to fight irregular wear and provides long life in trailer and all-position applications
- 5-rib design promotes premium handling and reduced noise
- Four steel belts provide casing strength for excellent durability, toughness and retreadability

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
8.25R15TR	14	K	33.2	9.1	16	6.50	15.4	627	57
8.25R15TR	18	J	33.2	9.1	16	6.50	15.4	627	57
10.00R15TR	16	K	36.3	10.8	16	7.50	17.0	570	70
10.00R15TR	18	J	36.3	10.8	16	7.50	17.0	570	70
7.50R16LT	14	J	31.7	8.3	16	6.00G	14.6	662	56
8R17.5	12	J	30.9	8.2	16	6.00	14.3	675	59
10R17.5	16	L	33.9	9.8	16	7.50HC	15.8	613	79
215/75R17.5	16	J	30.4	8.5	16	6.00	14.0	692	61
235/75R17.5	16	J	31.6	9.2	16	6.75	14.7	656	68
8R19.5	12	M	34.1	8.2	16	6.00	16.3	592	69
225/70R19.5	12	M	32.3	8.8	16	6.75	15.2	635	70
245/70R19.5	16	J	33.2	9.6	16	7.50	15.8	610	81
265/70R19.5	16	J	34.3	10	16	7.50	15.9	606	89
255/70R22.5	16	N	36.6	10	16	7.50	17.4	560	87
275/70R22.5	16	M	37.8	10.6	16	8.25	17.7	543	104

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

DRIVE

RLB400

ULTRA PREMIUM CLOSED SHOULDER
DEEP TREAD DRIVE POSITION TIRE



FEATURES & BENEFITS

- Closed-shoulder tread design provides even wear while maintaining excellent traction
- Extra deep $30/32$ " tread with stone drilling protectors to promote long original mileage
- Heavy duty casing for stability and promotion of retreading

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
11R22.5	14	J	42.0	10.9	30	8.25	20.1	488	127
11R22.5	16	J	42.0	10.9	30	8.25	20.1	488	130
295/75R22.5	14	J	41.2	11.7	30	9.00	19.4	498	129
11R24.5	14	J	43.9	10.9	30	8.25	21.1	466	139
11R24.5	16	J	43.9	10.9	30	8.25	21.1	466	141
285/75R24.5	14	J	42.1	11.0	30	8.25	19.8	485	131

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

DRIVE

RLB450

ULTRA PREMIUM OPEN SHOULDER
REGIONAL DRIVE POSITION TIRE



FEATURES & BENEFITS

- Innovative open shoulder tread design provides outstanding traction and promotes even wear
- $24/32$ " original tread depth for excellent mileage in long and short haul applications
- Heavy duty casing for stability and promotion of retreading

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
11R22.5	14	L	41.9	10.9	25	8.25	19.8	493	120
11R22.5	16	L	41.9	10.9	25	8.25	19.8	493	125
295/75R22.5	14	J	40.8	11.4	24	9.00	19.4	495	128
295/80R22.5	18	M	41.8	11.7	29	9.00	19.8	493	130
11R24.5	14	L	41.7	10.9	25	8.25	19.8	471	135
11R24.5	16	L	41.7	10.9	25	8.25	19.8	471	137
285/75R24.5	14	J	41.9	11.0	24	8.25	19.8	485	127
315/80R22.5	18	L	43.2	12.5	29	9.00	21.0	480	161

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

DRIVE

RLB490

PREMIUM LOW PROFILE
DRIVE POSITION MULTI-USE TIRE



FEATURES & BENEFITS

- Innovative tread design and compounds promotes excellent traction and resist irregular wear
- Durable casing construction perfect for tough regional and urban use
- Deep original tread depth provides maximum tread life

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
225/70R19.5	12	J	32.6	8.8	19	6.75	15.8	635	68
245/70R19.5	16	J	33.5	9.6	19	7.50	15.2	617	84
265/70R19.5	16	J	34.6	10	22	7.50	16.4	615	93
255/70R22.5	16	J	37.0	10	22	7.50	17.0	597	96
275/70R22.5	16	J	38.1	11	22	8.25	17.7	543	112

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

DRIVE

RLB1

PREMIUM OPEN SHOULDER
DRIVE POSITION TIRE



FEATURES & BENEFITS

- Open shoulder design provides excellent traction in wet and dry conditions; deep $\frac{26}{32}$ " tread depth for long original mileage
- Full-depth siping provides excellent performance throughout the life of the tread
- Heavy duty casing for stability and promotion of retreading
- Tubeless and tube-type sizes for special applications

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
225/70R19.5	12	J	32.6	8.8	19	6.75	15.8	635	68
245/70R19.5	16	J	33.5	9.6	19	7.50	15.2	617	84
9.00R20	16	J	40.6	10.1	26	7.00	19.1	505	119
10.00R20	16	J	41.5	10.7	22	7.50	19.4	497	134
1100R20	16	J	43.1	11.2	29	8.00	20.2	476	149
10R22.5	14	J	40.2	10.0	22	7.50	18.3	512	112
11R22.5	14	M	41.7	10.9	26	8.25	19.8	493	124
11R22.5	16	M	41.7	10.9	26	8.25	19.8	493	128
295/75R22.5	14	J	40.9	11.7	26	9.00	19.4	498	129
11R24.5	14	L	43.7	10.9	26	8.25	21.0	471	137
11R24.5	16	L	43.7	10.9	26	8.25	21.0	471	140
285/75R24.5	14	J	41.9	11.0	26	8.25	19.8	485	134

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

DRIVE

RLB200+

PREMIUM ON AND OFF HIGHWAY
DRIVE POSITION TIRE



FEATURES & BENEFITS

- Aggressive directional tread pattern for improved traction and handling
- Extra wide tread for enhanced tread life and handling

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
315/80R22.5	18	L	42.8	12.2	26	9.0	20.2	478	160
12.00R24	18	J	48.4	12.3	24	8.5	22.7	423	187
12.00R24	20	J	48.4	12.3	24	8.5	22.7	423	187
12R22.5	16	J	43.1	11.7	26	9.0	20.5	480	156
12R22.5	18	M	43.1	11.7	26	9.0	20.5	480	156

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

MIXED
SERVICE

RR202

ULTRA PREMIUM 5-RIB
HIGHWAY SERVICE TIRE



FEATURES & BENEFITS

- 10,000lb load carrying capacity for heavy load applications
- Modern multi-rib tread design excellent for free rolling applications
- Durable casing provides long original tread life and promotes multiple retreads

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
295/80R22.5	16	M	41.3	11.9	19	9	19.8	191	131
295/80R22.5	18	M	41.3	11.9	19	9	19.8	191	131
315/80R22.5	18	M	42.4	12.2	20	9	19.9	483	142
315/80R22.5	20	L	42.4	12.2	20	9	19.9	483	142
315/80R22.5	22	65MPH	42.4	12.2	20	9	19.9	483	147

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

MIXED
SERVICE

RR99/RR9

PREMIUM ON AND OFF HIGHWAY
MIXED SERVICE ALL-POSITION TIRE

FEATURES & BENEFITS

- Strong all-position tread pattern designed for multiple on and off highway uses
- Cut, chip and tear resistant tread compounds and heavy duty casing construction for excellent performance in tough applications
- 10,000lb load carrying capacity for heavy load applications

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD PER RADIUS	REVS PER MILE	WEIGHT
11R22.5	16	L	41.3	10.9	19	8.25	19.5	496	123
11R24.5	16	L	43.4	10.9	21	8.25	21.0	484	131
12R22.5	16	L	42.7	11.8	21	9.00	20.1	516	134
12R22.5	18	L	42.7	11.8	21	9.00	20.1	516	134
13R22.5	18	M	43.9	12.2	20	9.75	20.7	465	164
315/80R22.5	20	L	42.4	12.2	19	9.00	19.9	483	147
315/80R22.5	22	65MPH	42.4	12.2	20	9.00	19.9	483	147
9.00R20	14	M	40.2	10.1	19	7.00	18.9	510	110
10.00R20	16	K	41.3	10.7	20	7.50	19.4	497	140
11.00R20	16	K	42.7	11.1	20	8.00	20.1	478	155
12.00R20	18	L	44.0	11.7	20	8.50	20.6	466	164

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

MIXED
SERVICE

RLB900+

ULTRA PREMIUM WIDE BASE
MIXED SERVICE ALL-POSITION TIRE



FEATURES & BENEFITS

- Aggressive multi-purpose tread design ideal for on and off highway applications
- Large tread elements offer improved handling and excellent traction
- Heavy duty belt package and undertread offer increased durability, uniform wear and stability

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
385/65R22.5	18	K/L	42.2	14.8	22	11.75	20.1	483	164
385/65R22.5	20	K/L	42.2	14.8	22	11.75	20.1	483	164
425/65R22.5	20	K	44.6	16.3	22	13.00	21.2	458	205
445/65R22.5	20	J	45.3	17.9	22	14.00	20.9	457	229

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

MIXED
SERVICE

RR900/RR905

PREMIUM WIDE BASE
ALL-POSITION TIRE



FEATURES & BENEFITS

- Tread pattern and heavy ply rating designed for multiple uses
- 6-rib design excellent for free rolling applications
- Durable casing provides long original tread life and promotes multiple retreads

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
385/65R22.5	18	K/L	42	14.8	20	11.75	20.1	486	164
385/65R22.5	20	K/L	42	14.8	20	11.75	20.1	486	164
385/65R22.5	20	J	42	15.0	20	11.75	20.1	486	164

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

RLB600

PREMIUM EXTRA DEEP TREAD ON AND OFF HIGHWAY SEVERE SERVICE DRIVE POSITION TIRE



FEATURES & BENEFITS

- Extra deep $33/32$ " tread depth for on and off road applications
- Chip and cut resistant compounds offer long mileage and wear while reducing effect of cuts, snags and tears
- Aggressive tread offers excellent traction for severe off-highway use; no on-highway speed restriction

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD PER RADIUS	REVS PER MILE	WEIGHT
11R22.5	16	G	43	11.1	33	8.25	20.6	478	139
11R24.5	16	G	44	11.1	33	8.25	21.6	455	152

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

MIXED
SERVICE

RLB800

PREMIUM DEEP TREAD ON AND OFF
HIGHWAY SEVERE SERVICE DRIVE
POSITION TIRE



FEATURES & BENEFITS

- Chip, cut and abrasion resistant tread compounds
- Deep $29/32$ " tread depth promotes increased mileage and long service life
- Aggressive tread offers excellent traction for severe off-highway use; no on-highway speed restrictions

TIRE SIZE	PLY RATING	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	DESIGNED RIM	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
10.00R20	16	G	41.9	10.7	29	7.50	19.7	489	130
11R22.5	16	G	41.9	10.9	29	8.25	20.0	491	132
11R24.5	16	G	43.9	10.9	29	8.25	21.0	468	141
12.00R24 (NHS)	18	J	48.4	12.3	30	8.50	22.7	423	221

* Designed rim width. Please reference TRA specifications for all approved tire and rim combinations.

DOUBLE
COIN

LIMITED MANUFACTURER'S WARRANTY

LIMITED WARRANTY

Double Coin Radial TBR (Truck and Bus Radial) Tire Limited Manufacturer's Warranty January 1, 2011

TO OBTAIN AN ADJUSTMENT

- A. You must present the tire to be adjusted to a current Double Coin Commercial TBR Tire Dealer. (Please consult your telephone directory for locations or visit our dealer locator on our website at www.doublecoin-us.com). Tires replaced on an adjustment basis become the property of Double Coin.
- B. You must pay for taxes, fees or any additional services you order at the time of adjustment.
- C. No claim will be recognized unless submitted on a Double Coin claim form (supplied by the Double Coin Commercial TBR Tire Dealer), completely filled out and signed by you, the owner of the tire presented for adjustment, or your authorized agent.

FOR SERVICE ASSISTANCE OR INFORMATION

1. First contact the nearest Authorized Double Coin Commercial TBR Tire Dealer.
2. If additional assistance is required:
 - Visit our website at www.doublecoin-us.com.
 - E-mail The Double Coin Customer Relations Department at info@doublecoin-us.com or
 - Write to:
Double Coin Customer Assistance Service Department
406 E. Huntington Drive, Suite 200
Monrovia, CA 91016

WHO IS ELIGIBLE FOR WARRANTY COVERAGE

- You are eligible for the benefits of this warranty if you meet all the following criteria: You are the owner or authorized agent of the owner of new Double Coin Light Truck Radial or radial medium TBR tires.
- Your tires bear Department of Transportation (DOT) prescribed tire identification numbers and are not branded "NA" (Not Adjustable).
- Your Double Coin TBR tires have been used only on the vehicle on which they were originally installed according to the vehicle manufacturers or Double Coin's recommendations.
- Your tires were purchased on or after January 1, 2007.

WHAT IS COVERED UNDER THIS WARRANTY AND FOR HOW LONG

1. 50% FREE REPLACEMENT WARRANTY
If any Double Coin TBR tire covered by this warranty becomes unserviceable due to a defect in workmanship or material during the first 50% of the original tread life (calculated by subtracting one-half (1/2) the difference between the original new tire tread depth and 2/32" from the original new tire tread depth), then Double Coin will reimburse the cost of a replacement Double Coin TBR tire to you, plus the cost of mounting and balancing as follows:
 - a. The defective Double Coin tire must be replaced with a comparable new Double

Coin tire by an authorized Double Coin TBR tire dealer.

- b. Costs of mounting and balancing will be refunded up to a maximum of \$16.00 per tire.
 - c. Applicable taxes and fees will be the responsibility of the owner of the vehicle.
 - d. 50% free replacement applies to first quality tires only. Blemished, Non-Adjustable (stamped on tire), retreads or road hazard tires are specifically excluded.
2. PRORATED TIRE REPLACEMENT
Double Coin TBR tires covered by this warranty that become unserviceable due to a defect in workmanship or material during the life of the original usable tread (down to 2/32 remaining usable tread), will be reimbursed to the owner on a prorated basis. You pay only for the mounting, balancing, taxes and fees.

HOW TO CALCULATE THE PRORATED AMOUNT

The replacement price will be calculated by multiplying the current Double Coin "predetermined price for adjustment" or current advertised selling price at the adjustment location (whichever is lower) by the percentage of usable original tread that has been worn off at the time of adjustment. You pay for mounting, balancing, and amount equal to the full current Federal Excise Tax and any other applicable taxes and fees for the comparable new Double Coin replacement tire.

PRORATED REIMBURSEMENT EXAMPLE

If your disabled tire had an original 16/32" of usable tread depth and is worn to 8/32" of usable tread remaining you have used 50% and therefore must pay 50% of the predetermined price for adjustment or advertised selling price of a comparable tire, plus an amount equal to the full current Federal Excise Tax applicable to the comparable new replacement tire at the time of adjustment. If the price of the comparable tire is \$400.00, the cost to you would be \$200.00 plus Federal Excise Tax, mounting, balancing and any other applicable taxes.

DEFINITION OF A COMPARABLE TIRE

A "comparable" new Double Coin tire may either be the same line of tire or, in the event that the same tire is not available, a tire of the same basic construction and quality with a different sidewall or tread configuration. If a higher priced tire is accepted as replacement, the difference in price will be at an additional charge to you. Any replacement tire provided pursuant to this warranty will be covered by the Double Coin warranty in effect at the time of replacement.

WHAT THIS WARRANTY DOES NOT COVER

- Irregular wear or tire damage due to:
- Road hazards (including punctures, cuts, snags, impact breaks, etc.)
 - Wreck, collision, or fire.
 - Improper inflation, overloading, high speed spinup, misapplication, misuse, negligence,

DOUBLE
COIN

LIMITED MANUFACTURER'S WARRANTY

racing, chain damage, or improper mounting or demounting.

- Mechanical condition of the vehicle.
- Ride disturbance after the first $\frac{2}{32}$ " treadwear or due to damaged wheels or any vehicle condition.
- Any tire intentionally altered after leaving a factory producing Double Coin tires to change its appearance (example: white inlay on a black tire).
- Tires with weather cracking which were purchased more than five (5) years prior to presentation for adjustment. If you have no proof of purchase date, tires manufactured five (5) or more years prior to presentation are not covered.
- This limited warranty is applicable only in the United States and Canada and any tire used or equipped on a vehicle registered or operated outside the U.S. and Canada are not covered by this warranty.
- Tire branded or marked "Non-Adjustable (N/A) or "Blemished" (Blem)", or previously adjusted.
- Failure, damage, or irregular wear due to:
- Accident or vandalism, improper misalignment, wheel imbalance, faulty shocks or brakes;
- Mechanical condition of vehicle, including misalignment, wheel imbalance, faulty shocks or brakes;
- Misapplication of tire, use of improper inner tube;
- Alteration of the tire or addition of alien material or transfer from one vehicle to another;
- TBR tire failed due to faulty retreading or material.
- Cost of mounting and balancing service except as noted above.
- Loss of time or use, Inconvenience, or any incidental or consequential damages.
- Material added to a tire after leaving a factory producing Double Coin tires: (example: tire fillers, sealants, or balancing substances). If the added material is the cause of the tire being removed from service, the tire will not be adjusted.
- Loss of time, inconvenience, loss of use of vehicle, incidental or consequential damage.

THE DOUBLE COIN RADIAL CASING PROVISION

TBR Tire Casings will be warranted against defects in workmanship or material through 100% of the first and second retread for a period of five (5) years from the date of the casings DOT serial number or proof of purchase, if available, whichever comes first. If a Double Coin TBR tire dealer examines a casing and finds such a defect, Double Coin will reimburse the owner for the casing according to the following schedule:

DOUBLE COIN CASING VALUES	CASING VALUES (Double Coin)
DOUBLE COIN LIGHT TBR	
8, 8.5R17.5	\$15.00
8R19.5	\$15.00
TUBELESS	
9, 10, 11R17.5	\$20.00
9, 10R22.5	\$40.00
11R22.5, 24.5	\$65.00, \$70.00
12R22.5, 24.5	\$70.00

TUBELESS LOW PROFILE

215, 235/75R17.5	\$15.00
225, 245, 265	\$30.00
245, 265/75R22.5	\$15.00
255, 275/70R22.5	\$65.00
295/75R22.5	\$65.00
295/80R22.5	\$65.00
285/75R24.5	\$75.00
315/80R22.5	\$65.00
385, 425, 445/65R22.5	\$65.00
TUBE TYPE	
10.00R20	\$50.00

YOUR LEGAL RIGHTS

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusions may not apply to you. No representative or dealer has authority to make any representation, promise, or agreement on behalf of Double Coin, except as stated herein. Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the manufacturer. Under no circumstances is this a representation that a tire failure cannot occur. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state. This limited warranty is applicable only in the United States.

END OF WARRANTY

A tire has delivered its full original tread life and the new tire coverage of this warranty ends when the treadwear indicators become visible, or five (5) years from the date of original tire manufacture or new tire purchase date. (Without proof of purchase, date of manufacture will be used to determine age.) Casings may continue to be warranted beyond the new tire coverage. Please refer to the Radial Casing Provision for warranty details on casings.

SAFETY WARNINGS

Serious injury or property damage may result from:

- TIRE FAILURE DUE TO UNDERINFLATION/ OVERLOADING. Follow the owner's manual or tire placard in vehicle.
- TIRE FAILURE DUE TO EXCESSIVE HIGH SPEED. Follow the owner's manual or tire placard in vehicle.
- EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING. Only specially trained persons should mount tires.
- FAILURE TO MOUNT RADIAL TIRES ON APPROVED RIMS
- FAILURE TO DEFLATE SINGLE OR DUAL ASSEMBLIES COMPLETELY BEFORE DISMOUNTING.
- TIRE SPINNING. On slippery surfaces such as snow, mud, ice, etc., do not spin tires in excess of 35 mph (55 kpm), as indicated on the speedometer. Personal injury and severe damage may result from excessive wheel spinning, including tire disintegration or axle failure.

DOUBLE COIN

406 E. Huntington Drive, Suite 200
Monrovia, CA 91016
1-888-226-5250
www.doublecoin-us.com

2012

THE SMART MONEY IS ON



406 E. Huntington Drive, Suite 200
Monrovia, CA 91016
1-888-226-5250
www.doublecoin-us.com